

Aqua-Add M

8126

Additive to help prevent stain formation on account of metal contamination during the **application of stains**, for use in **industry and trade**

PRODUCT DESCRIPTION


Product numbers

8126000210

General

Special additive solution to prevent stain formation caused by tiny metal contaminants from wood processing (e.g. blades from veneer cutting, sanding with steel wool) of veneers and solid wood when using hardwoods that have a high tannin content, such as oak and ash. Contamination with metal filings becomes recognisable when the wood is rinsed with water or a stain is tested out on the original wood. The product does not have any effect on the colour of the stain.

Application area



Additive for the water-based hardwood stain Arova Colora (1326), for use in furniture and interior finishing.

PROCESSING

Processing instructions



- Please shake / stir the product before use.
- The temperature of the product and object, and the room temperature must be at least + 15 °C.
- Carefully stir the product into the stain.
- Use only in combination with the base materials recommended by ADLER.
- Mixed paints and stains must be processed as specified in the corresponding technical data sheet.
- The mixtures are all usable for one week.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result.
- Please observe our **ARL 110 - Working guidelines for staining Wood**.


Quantity to be added



Quantity to be added: 4% by weight

Therefore please contact your sales representative.

Cleaning the working equipment



8029

With water immediately after use.

To remove dried paint residues we recommend using Aqua-Cleaner (8029) (diluted 1:1 with water).

ORDERING INFORMATION

Size of trading unit

500 ml

Supplementary products

Aqua-Cleaner 8029 (8029)
Arova Colora (1326)

Please refer to the corresponding technical data sheets of the products.

FURTHER DETAILS

Durability / storage



Min. 1 year(s) in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Close opened containers well and use up the content as soon as possible.

Safety information



The product is only suitable for the industrial and professional use.

The inhalation of paint aerosols during spray application must generally be avoided. This is ensured by the proper use of a respirator (combination filter A2/P2).

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at www.adler-lacke.com.