

Aquafix ST

8141

Texture paste for water-based coating systems by ADLER, for use in industry and trade

PRODUCT DESCRIPTION

General

Texture paste for colourless and pigmented water-based coating systems such as Bluefin Unistar (2965), Bluefin Pigmcryl NG in various qualities (3200) or Aquawood Protor Finish D NG (5808). Creates hard-wearing surfaces with a textured effect, for use in all interior settings and in protected outdoor settings.

Application area

Texture paste for water-based paints.



PROCESSING

Processing instructions



- Please shake the product before use.
- Carefully stir the Aquafix ST (8141) into the unhardened and undiluted paint/varnish; then stir in the hardener and the required quantity of thinner.
- Mixed paints and stains must be processed as specified in the corresponding technical data sheet.
- Aquafix ST (8141) will result in a noticeable reduction in the degree of gloss of the original paint/varnish – depending on the amount used.
- You can paint over coats of paint/varnish with Aquafix ST (8141) (without intermediate sanding, within 24 hours); the degree of texture will, however, be somewhat reduced.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result.

Quantity to be added



Max. 4 - 5 % by weight of the paint/varnish.

Depending on the coating system, the following additional quantities are recommended:


Water-based ADLER furniture paints/varnishes:	5 %
System Aquawood Protor-Finish:	4 %

Drying times

(at 23 °C and 50 % rel. humidity)

The drying behaviour of the coating system is not affected by the addition of Aquafix ST (8141).

Cleaning the working equipment



With water immediately after use.

To remove dried paint residues we recommend using Aqua-Cleaner (8029) (diluted 1:1 with water).

ORDERING INFORMATION

Size of trading unit


1 kg

Finer points

Aquafix ST Sehr Grob ST10 (8141040810)
Aquafix ST Grob ST30 (8141040830)
Aquafix ST# Mittलगrob ST50 (8141040850)
Aquafix ST Fein ST70 (8141040870)
Aquafix ST Sehr Fein ST90 (8141040890)

FURTHER DETAILS

Durability / storage



Min. 6 month(s) in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Close opened containers well and use up the content as soon as possible.

Safety information



The product is only suitable for the industrial and professional use.

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at www.adler-lacke.com.