Technical data sheet



Arova Aqua-Additive

8116

Water-based additive for wood stains, for use in industry and trade

	PRODUCT DESCRIPTION		
General	Colourless additive for water-based Arova stain systems to improve the stain finish/lengthen the time for which the product is still wipeable.		
Application area	Additive for water-based Arova stain systems.		
	Arova Aqua-Additive Beizzusatz 89344 (8116040775): To improve the evenness of the stain finish of Arova Classic (1333)		
	Arova Aqua-Additive Wischzusatz Flex (8116040776): To improve the open time (time for which the product is still wipeable) of Arova Flex (1340).		

PROCESSING

Processing instructions





- Please shake the product before use.
- Carefully stir the product into the stain.
- Use only in combination with the base materials recommended by ADLER.
- Stains that have been mixed must be used according to the instructions in the relevant Technical Data Sheet.
- The mixtures remain usable for 12 weeks.
- Prior to applying the stain and the coating, you should always stain a sample on the original wood and treat it with the intended coating material in order to assess the final colour shade. Only use stains from the same batch for a commission.
- Any change in the processing sequence, environmental conditions, nonobservance of instructions or the use of products not listed may have an unfavourable effect on the result.

Quantity to be added



Depending on the Arova Aqua additive and stain used, the following quantities are recommended for the additive:

Arova Aqua-Additive Beizzusatz 89344 (8116040775)	up to a maximum of 10 %	of Arova (1333)	Classic
Arova Aqua-Additive Wischzusatz Flex (8116040776)	up to a maximum of 20 %	of Arova (1340)	Flex

Greater amounts should not be added as this can lead to problems with adhesion.

Drying times

(at 23 °C and 50 % rel. humidity)

The drying properties of the stains are not affected by the addition of Arova Aqua additives.

1-0 IMC 8116 | 06/25

Cleaning the working equipment





With water immediately after use.

To remove dried paint residues we recommend using Aqua-Cleaner (8029) (diluted 1:1 with water).

	ERIN	C. IN	$\Lambda\Lambda\Lambda$	ION
OND		יוו טו	/V\/\	

Size of trading unit

11

Product variants

Arova Aqua-Additive Beizzusatz 89344 (8116040775) Arova Aqua-Additive Wischzusatz Flex (8116040776)

FURTHER DETAILS

Durability / storage







Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 $^{\circ}$ C).

Safety information



The product is only suitable for the industrial and professional use.

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at **www.adler-lacke.com**.