

## Clean Abbeizer-Spray

8311


Universal paint remover for DIY and professional use

### PRODUCT DESCRIPTION

#### General

Highly effective paint stripper spray with a gel structure, also suitable for vertical surfaces. Particularly suitable for removing old, water-based window coating systems. Due to its long open time, it removes even thick coating layers in a single operation and is also effective on many two-component systems (carry out a preliminary test). The product is formulated without the addition of chlorinated hydrocarbons.


#### Application area



For stripping coated small-area objects, such as e.g. wooden windows, front doors, furniture, railings, frames, fittings, etc.

### PROCESSING

#### Processing instructions



- Please shake the product before use.
- The temperature of the product and object, and the room temperature must be at least + 5 °C.
- The optimal conditions for use are between 15 - 25 °C with a relative atmospheric humidity between 40 - 80 %.
- It is recommended to check material compatibility on test surfaces.
- Sealants and other solvent-sensitive parts must be masked off.
- Non-ferrous metals may be discoloured by Clean Abbeizer-Spray (8311).
- Dwell time approx. 10 minutes per coating.
- The dwell time depends on the type, layer thickness, working temperature and age of the coating. The optimal dwell time is best determined on a trial area.
- Highly absorbent substrates reduce the dwell time.
- Avoid direct sunlight!
- Remove the swollen old coating using Lackziehklinge (9504) or a stripping scraper.
- Rinse the stripped surfaces thoroughly with water to prevent discolouration of subsequent coating applications.
- Apply the product generously to achieve full performance and additionally cover the surface with foil.

**Application technique**

	<b>Spraying</b>
<b>Application quantity per coat (ml/m<sup>2</sup>)</b>	300–500

The product is ready to use.

Apply the product generously.

The shape and surface condition of the workpiece as well as the type of application influence the actual consumption. Accurate values for consumption must be obtained by applying trial coats in advance.

**ORDERING INFORMATION****Size of trading unit**

400 ml (Contents sufficient for approx. 0.8 m<sup>2</sup>)

**Colour shades / Glosslevels**

**Standard products:**  
Clean Abbeizer-Spray (8311080969)

**Supplementary products**

Lackziehklinge (9504)  
Please refer to the corresponding technical data sheets of the products.

**FURTHER DETAILS****Durability / storage**

Min. 2 year(s) in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

**Safety information**

The inhalation of paint aerosols during spray application must generally be avoided. This is ensured by the proper use of a respirator (combination filter A2/P2).

The removed coating sludge must be classified as hazardous waste and disposed of in accordance with legal regulations.

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at [www.adler-lacke.com](http://www.adler-lacke.com).