

ADLER-Werk Lackfabrik Johann Berghofer GmbH & Co KG Bergwerkstraße 22 6130 SCHWAZ Österreich

Test Report No. 59568-A002-AgBB-L

Test objective:

Evaluation according to AgBB scheme 2024

Lignovit Primo

Date of report:

06/12/2024

Number of pages of report:

20

Testing / responsible laboratory:

eco-INSTITUT Germany GmbH, Köln

Test objective fulfilled:

The test results in the report refer exclusively to the test

The test results in the report refer exclusively to the test sample submitted by the manufacturer. The report is not permitted to be used in product and company advertising. The report may be published in full as technical documentation on the Internet with the written consent of eco-INSTITUT Germany GmbH. eco-INSTITUT Germany GmbH has recommended that the manufacturer repeats the test after 3 years at the latest. More information at www.eco-institut.de/en/advertising





Content

Sample View	3
Statement of conformity with AgBB 2024	
Summary statement of conformity with AgBB 2024	
Laboratory report	6
1 Emission analysis	6
1.1 Sample A002, Volatile organic compounds after 3 days	7
1.2 Sample A002, Volatile organic compounds after 28 days	11
Appendix	14
Sampling sheet	14
List of calibrated Volatile Organic Compounds (VOC)	15
Definition of terms	
Commentary on emission analysis	19
Explanation of Specific Emission Rate SER	20



Sample View

Internal sample number (filled in by laboratory)

Photo of the test specimen: A002

Article designation according to order:

Sample/batch number according to order:

Type of sample:

Date of production:


Sampling by:

Date of sampling:

Location of sampling:

Receipt of sample / Condition upon delivery:

59568-A002



Lignovit Primo

#416969

2 identically coated glass plates to 20 cm x 20 cm (#2a und #2b)

18.09.2024

Peter Passler, M.Sc.

07/10/2024

Labor Entwicklung Fenster- und Bautenlacke

14/10/2024 / Sample is not packed separately from A002, test specimen labelled.



Statement of conformity with AgBB 2024

The sample with the internal sample number 59568-A002 has been tested on behalf of **ADLER-Werk Lackfabrik Johann Berghofer GmbH & Co KG**. The article description according to the order is **Lignovit Primo**.

This evaluation is based on the test criteria of the scheme "Health-related Evaluation of Emissions of Volatile Organic Compounds (VVOC, VOC and SVOC) from Building Products" of the Committee for Health-Related Evaluation of Building Products (AgBB 2024).

The results documented in the test report were evaluated as follows.¹

Test parameter	Result	Requirement	Requirement hold [yes/no]
Emission analysis			
Measurement time: 3 days after test chamber loading			
Sum VOC (C6-C16) ¹⁾	0.056 mg/m³	≤ 10 mg/m³	yes
Carcinogenic substances, cat. 1A and 1B acc. to Regulation (EC) No. 1272/2008 (and TRGS 905) (per substance)	≤ 0.01 mg/m³	≤ 0.01 mg/m³	yes
Measurement time: 28 days after test chamber loading			
Sum VOC (C6-C16) including SVOC with LCI ¹⁾	< 0.005 mg/m³	≤ 1.0 mg/m³	yes
Sum SVOC without LCI (C16-C22) 1)	0.011 mg/m³	≤ 0.1 mg/m³	yes
R-value (dimensionless)	0.00	≤ 1	yes
Sum VOC without LCI	< 0.005 mg/m³	≤ 0.1 mg/m³	yes
Carcinogenic substances, cat. 1A and 1B acc. to Regulation (EC) No. 1272/2008 (and TRGS 905) (per substance)	≤ 0.001 mg/m³	≤ 0.001 mg/m³	yes

¹⁾ For sum VOC (C6-C16) and sum SVOC (C16-C22) only substances \geq 5 $\mu g/m^3$ are considered.

 $^{^1}$ If a measurement result that slightly exceeds the specification is assessed as "not fulfilled", this is based on the agreement of the "shared risk of measurement uncertainty (shared risk approach)". According to this, the probability that the statement is correct is ≥ 50 %. Similarly, a result slightly below the specification value also only has a probability of ≥ 50 % of being compliant. I.e., the risk of making a false negative statement regarding the fulfilment of the specification is just as high as the risk of making a false positive statement (more information at https://www.eco-institut.de/en/2019/07/measurement_uncertainty/).



Summary statement of conformity with AgBB 2024

The sample with the internal sample number 59568-A002, article description according to order: **Lignovit Primo**, meets the emission requirements of the AgBB scheme.

Cologne, 06/12/2024

Nora Rasch,

(Project management)



Laboratory report

1 Emission analysis

Test method

DIN EN 16516:2020-10 Testing and evaluation of the release of dangerous substances;

determination of emissions into indoor air

A002, Preparation of test specimen

Date: 09/10/2024

Test specimen preparation: Applied by the customer: Application of the first layer on glass with a cup

gun on 09/10/2024: Application quantity 60 g/m^2 ; Intermediate drying between 1st and 2nd layer for 8 hours; Application of the second layer on 09/10/2024: Application quantity 60 g/m^2 ; drying / pre-conditioning for 16 h, subsequently packed; Shipping on 10/10/2024; Sample receipt

Laboratory on 14/10/2024

Masking of backside: not applicable
Masking of edges: not applicable
Relationship of unmasked not applicable

edges to surface:

Loading reference unit: area-specific [m²]
Dimensions: 20.0 cm x 20.0 cm

A002, Test chamber conditions according to DIN EN ISO 16000-9:2024-08

Chamber volume: 0.100 m³ 23 °C ± 1 °C Temperature: Relative humidity: 50 % ± 1 % Air pressure: normal Air: cleaned $0.5 h^{-1}$ Air change rate: 0.3 m/sAir velocity: Loading: $0.4 \text{ m}^2/\text{m}^3$ Specific air flow rate: $1.25 \text{ m}^3/(\text{m}^2 \cdot \text{h})$

Air sampling: 3 days after test chamber loading

28 days after test chamber loading

Analytics

Starting time of the test (t0):

Aldehydes and ketones: DIN ISO 16000-3:2023-12

Limit of quantification: 2 µg/m³

Volatile organic compounds: DIN ISO 16000-6:2022-03

Limit of quantification: 1 µq/m³ (1,4-Cyclohexanedimethanol, Diethylene glycol,

15/10/2024

1,4-Butanediol: 5 µg/m³)

Note for analysis: not specified



1.1 Sample A002, Volatile organic compounds after 3 days

Test objective:

Volatile organic compounds (VOC), test chamber, air sampling 3 days after test chamber loading

Test result:

Internal sample number: 59568-A002

	Substance	CAS No.	RT [min]	Concentration+ calib. substances $\geq 1 \mu g/m^3$ uncalib. substances $\geq 1 \mu g/m^3$ DNPH $\geq 2 \mu g/m^3$ [$\mu g/m^3$]	Toluene- equivalent substances ≥ 5 μg/m³ [μg/m³]	SER+ [µg/(m²-h)]	CMR Classifi- cation++	LCI AgBB 2024 [μg/m³]	R-value
	Aldehydes								
VOC	Pentanal (Valeraldehyde)	110-62-3	6.57	5	< 5	6.3		800	0.01
VOC	Hexanal	66-25-1	8.78	36	18	45		900	0.04
VOC	Heptanal	111-71-7	11.14	1	< 5	1.3		900	0.00
VOC	Nonanal	124-19-6	15.69	2	< 5	2.5		900	0.00
VOC	2-Octenal	2548-87-0	14.74	1	< 5	1.3		18	0.06
VVOC	Acetaldehyde	75-07-0		2	n. d.	< 2.9	Carc. 1B Muta. 2	300	0.01
VVOC	Formaldehyde	50-00-0		2	n. d.	< 2.9	Carc. 1B Muta. 2	100	0.02
	Acids								
VOC	n-Caproic acid (n-Hexanoic acid)	142-62-1	12.33	3	< 5	3.8		2100	0.00
	Others								
VOC	Octamethylcyclotetrasiloxane (D4)	556-67-2	12.50	1	< 5	1.3	Repr. 2	1200	0.00
VOC	Decamethylcyclopentasiloxane (D5)	541-02-6	15.83	1	< 5	1.3		1500	0.00
	Other identified substances in addition to LCI list								
VOC	m/z 91 61 75*		5.82	1	< 5	1.3			
VOC	m/z 43 56 98*		8.02	1	< 5	1.3			



	Substance	CAS No.	RT	Concentration+ calib. substances ≥ 1 µg/m³	Toluene- equivalent	SER+	CMR Classifi- cation++	LCI AgBB 2024	R-value
				uncalib. substances ≥ 1 µg/m³	substances ≥ 5 μg/m³				
				DNPH $\geq 2 \mu g/m^3$					
			[min]	[µg/m³]	[µg/m³]	[µg/(m²·h)]		[µg/m³]	
VOC	several unidentified substances*		11- 22.14	15	15	19			
SVOC	Glutaric acid ester m/z 115 87 171*		26.02	1	< 5	1.3			
SVOC	Ester m/z 165 182 57*		26.32	20	20	25			

⁺ identified and calibrated substances, substance specific calculated

⁺⁺ classification according to Regulation (EG) N° 1272/2008: Categories Carc. 1A, 1B and 2, Muta. 1A, 1B and 2, Repr. 1A, 1B and 2, TRGS 905: K1A, K1B, K2, M1A, M1B, M2, R1A, R1B, R2; IARC: Group 1, 2A, 2B and 3, DFG MAK-list: Categorie III1 to III5

* unidentified substances, calculated as toluene equivalent reported with significant mass fragments as mass-to-charge ratio (m/z)

n. d.: not determined



Carcinogenic, mutagenic, and reproductive toxic compounds*	Concentration after 3 days [µg/m³]	SERa [µg/(m² • h)]
CMR 1: VOC (incl. VVOC and SVOC) with the following categorisations: Regulation (EC) No. 1272/2008: Category Carc. 1A and 1B, Muta. 1A and 1B, Repr. 1A and 1B; TRGS 905: K1A, K1B, M1A, M1B, R1A, R1B; IARC: Group 1 and 2A; DFG (MAK list): Categories III1, III2 (sum)	< 1	< 1.3
C 1: VOC (incl. VVOC and SVOC) with the following categorisations: Regulation (EG) Nr. 1272/2008: Category Carc. 1A u. 1B; TRGS 905: K1A, K1B (sum)	< 1	< 1.3

TVOC, Total volatile organic compounds	Concentration after 3 days [µg/m³]	SERa [µg/(m² • h)]
Sum of VOC according to DIN EN 16516	33	41
Sum of VOC according to AgBB 2024	56	70
Sum of VOC according to eco-INSTITUT-Label	67	84
Sum of VOC according to DIN ISO 16000-6	52	65

TSVOC, Total semi volatile organic compounds	Concentration after 3 days [µg/m³]	SERa [µg/(m² • h)]
Sum of SVOC according to DIN EN 16516	20	25
Sum of SVOC without LCI according to AgBB 2024	20	25
Sum of SVOC without LCI according to eco-INSTITUT-Label	21	26
Sum of SVOC with LCI according to AgBB 2024	< 5	< 6.3

TVVOC, Total very volatile organic compounds	Concentration after 3 days [µg/m³]	SERa [µg/(m² • h)]
Sum of VVOC according to AgBB 2024	< 5	< 6.3
Sum of VVOC according to eco-INSTITUT-Label	4	5

^{*}Excluding formaldehyde and acetaldehyde (Carc. 1B) due to an assumed "practical threshold" under which a significant carcinogenic risk is no longer to be expected (see Federal Institute for Risk Assessment (2006): Toxicological evaluation of formaldehyde and Federal Environment Agency (2016): Reference value for formaldehyde in indoor air and protocol of the 11th meeting of 'Ausschusses für Innenraumrichtwerte' (AIR), 11/2020). In the case of a toxicological emission assessment, a single-substance analysis of the concentrations is necessary.

In the opinion of the committee for Indoor Air Guide Values (Ausschuss für Innenraumrichtwerte) of the Federal Environment Agency, the concentration of 0.1 mg formaldehyde/m³ indoor air, based on a measurement period of half an hour, should not be exceeded, also for a short time (Bundesgesundheitsblatt 2016 · 59: 1040-1044 DOI 10.1007 / s00103 ·016-2389-5 © Springer-Verlag Berlin Heidelberg 2016).



Other sums of VOC	Concentration after 3 days [µg/m³]	SERa [µg/(m² • h)]
VOC without LCI according to AgBB 2024 (sum)	15	19
VOC without LCI according to eco-INSTITUT-Label (sum)	17	21
CMR 2: VOC (incl. VVOC and SVOC) with the following categorisations: Regulation (EC) No. 1272/2008: Category Carc. 2, Muta. 2, Repr. 2; TRGS 905: K2, M2, R2; IARC: Group 2B; DFG (MAK list): Category III3 (sum)	5	6.3
Sensitising compounds with the following categorisations: DFG (MAK list): Category IV; Regulation (EC) No. 1272/2008: skin sensitising, respiratory sensitising; TRGS 907 (sum)	7	8.8
Bicyclic Terpenes (sum)	<1	< 1.3
C9 - C14 Alkanes / Isoalkanes as dekane-equivalent (sum)	<1	< 1.3
C4 - C11 Aldehydes, acyclic, aliphatic (sum)	45	56
C9 - C15 Alkylated benzenes (sum)	<1	< 1.3
Cresols (sum)	<1	< 1.3

Risk value for assessment of LCI	R-value
R-value according to eco-INSTITUT-Label	0.13
R-value according to AgBB 2024	0.05
R-value according to Belgian regulation	0.05
R-value according to EU-LCI	0.05

Note:

Due to different requirements in the respective guidelines, the calculation of TVOC, TVVOC, TSVOC and R-value may result in different values.

Short-chain carbonyl compounds (C1-C5) are quantified via HPLC acc. to DIN ISO 16000-3:2013-01. Therefore, no toluene equivalents are given for VVOC. These substances are taken into concern by means of their substance specific calibration via the sum of VVOC acc. to DIN EN 16516:2020-10. For VOC however, the substance specific calibration takes place via HPLC whereas the TVOC is calculated using the toluene equivalent determined via Tenax acc. to DIN EN 16516:2020-10.



1.2 Sample A002, Volatile organic compounds after 28 days

Test objective:

Volatile organic compounds (VOC), test chamber, air sampling 28 days after test chamber loading

Test result:

Internal sample number: 59568-A002

	Substance	CAS No.	RT	Concentration+	Toluene-	SER+	CMR	LCI	R-value
				calib. substances ≥ 1 μg/m³	equivalent		Classifi- cation++	AgBB 2024	
				uncalib. substances ≥ 1 μg/m³	substances ≥ 5 µg/m³				
				DNPH ≥ 2 μg/m³					
			[min]	[µg/m³]	[µg/m³]	[µg/(m²·h)]		[µg/m³]	
	Aldehydes								
VOC	Hexanal	66-25-1	8.76	3	< 5	3.8		900	0.00
	Others								
VOC	Decamethylcyclopentasiloxane (D5)	541-02-6	15.82	1	< 5	1.3		1500	0.00
	Other identified substances in addition to LCI list								
VOC	m/z 43 56 98*		8.02	1	< 5	1.3			
SVOC	Glutaric acid ester m/z 115 87 171*		26.02	1	< 5	1.3			
SVOC	Ester m/z 165 182 57*		26.32	11	11	14			
SV0C	m/z 112 226 281*		27.13	2	< 5	2.5			

⁺ identified and calibrated substances, substance specific calculated

⁺⁺ classification according to Regulation (EG) N° 1272/2008: Categories Carc. 1A, 1B and 2, Muta. 1A, 1B and 2, Repr. 1A, 1B and 2, TRGS 905: K1A, K1B, K2, M1A, M1B, M2, R1A, R1B, R2; IARC: Group 1, 2A, 2B and 3, DFG MAK-list: Categorie III1 to III5

^{*} unidentified substances, calculated as toluene equivalent reported with significant mass fragments as mass-to-charge ratio (m/z)

n. d.: not determined



Carcinogenic, mutagenic, and reproductive toxic compounds*	Concentration after 28 days [µg/m³]	SERa [µg/(m² • h)]
CMR 1: VOC (incl. VVOC and SVOC) with the following categorisations: Regulation (EC) No. 1272/2008: Category Carc. 1A and 1B, Muta. 1A and 1B, Repr. 1A and 1B; TRGS 905: K1A, K1B, M1A, M1B, R1A, R1B; IARC: Group 1 and 2A; DFG (MAK list): Categories III1, III2 (sum)	<1	< 1.3
C 1: VOC (incl. VVOC and SVOC) with the following categorisations: Regulation (EG) Nr. 1272/2008: Category Carc. 1A u. 1B; TRGS 905: K1A, K1B (sum)	<1	< 1.3

TVOC, Total volatile organic compounds	Concentration after 28 days [µg/m³]	SERa [µg/(m² • h)]
Sum of VOC according to DIN EN 16516	< 5	< 6.3
Sum of VOC according to AgBB 2024	< 5	< 6.3
Sum of VOC according to eco-INSTITUT-Label	5	6.3
Sum of VOC according to DIN ISO 16000-6	14	18

TSVOC, Total semi volatile organic compounds	Concentration after 28 days [µg/m³]	SERa [µg/(m² • h)]
Sum of SVOC according to DIN EN 16516	11	14
Sum of SVOC without LCI according to AgBB 2024	11	14
Sum of SVOC without LCI according to eco-INSTITUT-Label	14	18
Sum of SVOC with LCI according to AgBB 2024	< 5	< 6.3

TVVOC, Total very volatile organic compounds	Concentration after 28 days [µg/m³]	SERa [µg/(m² • h)]
Sum of VVOC according to AgBB 2024	< 5	< 6.3
Sum of VVOC according to eco-INSTITUT-Label	< 1	< 1.3

^{*}Excluding formaldehyde and acetaldehyde (Carc. 1B) due to an assumed "practical threshold" under which a significant carcinogenic risk is no longer to be expected (see Federal Institute for Risk Assessment (2006): Toxicological evaluation of formaldehyde and Federal Environment Agency (2016): Reference value for formaldehyde in indoor air and protocol of the 11th meeting of 'Ausschusses für Innenraumrichtwerte' (AIR), 11/2020). In the case of a toxicological emission assessment, a single-substance analysis of the concentrations is necessary.

In the opinion of the committee for Indoor Air Guide Values (Ausschuss für Innenraumrichtwerte) of the Federal Environment Agency, the concentration of 0.1 mg formaldehyde/m³ indoor air, based on a measurement period of half an hour, should not be exceeded, also for a short time (Bundesgesundheitsblatt 2016 · 59: 1040-1044 DOI 10.1007 / s00103 ·016-2389-5 © Springer-Verlag Berlin Heidelberg 2016).



Other sums of VOC	Concentration after 28 days [µg/m³]	SERa [µg/(m² • h)]
VOC without LCI according to AgBB 2024 (sum)	< 5	< 6.3
VOC without LCI according to eco-INSTITUT-Label (sum)	1	< 1.3
CMR 2: VOC (incl. VVOC and SVOC) with the following categorisations: Regulation (EC) No. 1272/2008: Category Carc. 2, Muta. 2, Repr. 2; TRGS 905: K2, M2, R2; IARC: Group 2B; DFG (MAK list): Category III3 (sum)	<1	< 1.3
Sensitising compounds with the following categorisations: DFG (MAK list): Category IV; Regulation (EC) No. 1272/2008: skin sensitising, respiratory sensitising; TRGS 907 (sum)	<1	< 1.3
Bicyclic Terpenes (sum)	<1	< 1.3
C9 - C14 Alkanes / Isoalkanes as dekane-equivalent (sum)	<1	< 1.3
C4 - C11 Aldehydes, acyclic, aliphatic (sum)	3	3.8
C9 - C15 Alkylated benzenes (sum)	<1	< 1.3
Cresols (sum)	<1	< 1.3

Risk value for assessment of LCI	R-value
R-value according to eco-INSTITUT-Label	0.00
R-value according to AgBB 2024	0.00
R-value according to Belgian regulation	0.00
R-value according to EU-LCI	0.00

Note:

Due to different requirements in the respective guidelines, the calculation of TVOC, TVVOC, TSVOC and R-value may result in different values.

Short-chain carbonyl compounds (C1-C5) are quantified via HPLC acc. to DIN ISO 16000-3:2013-01. Therefore, no toluene equivalents are given for VVOC. These substances are taken into concern by means of their substance specific calibration via the sum of VVOC acc. to DIN EN 16516:2020-10. For VOC however, the substance specific calibration takes place via HPLC whereas the TVOC is calculated using the toluene equivalent determined via Tenax acc. to DIN EN 16516:2020-10.

Cologne, 06/12/2024

Michael Stein, Dipl.-Chem. (Laboratory Management)



Appendix

Sampling sheet





List of calibrated Volatile Organic Compounds (VOC)

Aromatic hydrocarbons (31)

Benzene⁴

1,2,3-Trimethylbenzene 1,2,4-Trimethylbenzene 1,3,5-Trimethylbenzene 1-Isopropyl-2-methylbenzene 1-Isopropyl-4-methylbenzene

1,2,4,5-Tetramethylbenzene

Ethylbenzene n-Propylbenzene Isopropylbenzene (Cumene)⁴

1,3-Diisopropylbenzene 1,4-Diisopropylbenzene n-Butylbenzene

1-Propenylbenzene (beta-Methylstyrene)

Toluene 2-Ethyltoluene Vinyltoluene o-Xylene m-/p-Xylene Styrene Phenylacetylene

2-Phenylpropene (alpha-Methylstyrene)

4-Phenylcyclohexene 1-Phenyloctane 1-Phenyldecane² 1-Phenylundecane² Indene Naphthalene 1-Methylnaphthalene 2-Methylnaphthalene 1,4-Dimethylnaphthalene

Aliphatic hydrocarbons (23)

2-Methylpentane 3-Methylpentane¹ Methylcyclopentane n-Hexane Cyclohexane Methylcyclohexane 1,4-Dimethylcyclohexane n-Heptane

2,2,4,6,6-Pentamethylheptane

n-Octane n-Nonane n-Decane n-Undecane n-Dodecane n-Tridecane n-Tetradecane n-Pentadecane n-Hexadecane Decahydronaphthalene 1-Octene

1-Decene 1-Dodecene 4-Vinylcyclohexene

Terpenes (12)

delta-3-Carene alpha-Pinene beta-Pinene alpha-Terpinene Longipinene Limonene Longifolene Isolongifolene beta-Caryophyllene alpha-Phellandrene Myrcene

Aliphatic alcohols and ether (18)

1-Propanol¹ 2-Propanol¹ 2-Methyl-1-propanol 1-Butanol tert-Butanol 1-Pentanol 1-Hexanol Cyclohexanol 2-Ethyl-1-hexanol 1-Heptanol 1-Octanol 1-Nonanol 1-Decanol

Camphene

Fthanol

1,4-Cyclohexandimethanol 4-Hydroxy-4-methyl-pentan-2-one

(Diacetone alcohol)

Methyl-tert-butyl ether (MTBE)1

Tetrahydrofuran (THF)

Aromatic alcohols (phenoles) (8)

Furfuryl alcohol Benzyl alcohol Phenol 2-Phenylphenol (oPP)

BHT (2,6-Di-tert-butyl-4-methylphenol)

o-Cresol m-/p-Cresol

4-Chloro-3-methylphenol (Chlorocresol)

Glycols, Glycol ether, Glycol ester (49)

Ethyleneglycol (Ethan-1,2-diol) Propylenglycol (Propane-1,2-diol)

Diethylene glycol Dipropylene glycol Neopentyl glycol Hexyleneglycol Ethyldiglycol

Ethylene glycol monobutyl ether Diethylene glycol methyl ether Diethylene glycol monobutyl ether Diethylene glycol phenyl ether Dipropylene glycol-dimetyl ether

Dipropylene glycol mono-n-butyl ether Dipropylene glycol mono-tert-butyl ether Dipropylene glycol monomethyl ether Dipropylene glycol mono-n-propyl ether Tripropylene glycol monomethyl ether Triethylene glycol dimethyl ether 1,2-Propylene glycol dimethyl ether 1,2-Propylene glycol-n-propyl ether 1,2-Propylene glycol-n-butyl ether

Butyl glycolate 2-Methoxyethanol 2-Ethoxyethanol 2-Methylethoxyethanol 2-Propoxyethanol 2-Hexoxyethanol 2-(2-Hexoxyethoxy)ethanol

2-Phenoxyethanol 1-Methoxy-2-propanol 2-Methoxy-1-propanol 1-Ethoxy-2-propanol 1-tert-Butoxy-2-propanol 3-Methoxy-1-butanol 1,4-Butanediol 1,2-Dimethoxyethane 1,2-Diethoxyethane

1-Methoxy-2-(2-methoxy-ethoxy)ethane

Ethylene carbonate Propylene carbonate 2-Methoxy-1-propyl acetate

Diethylene glycol monomethyl ether acetate

2-Methoxyethyl acetate 2-Ethoxyethyl acetate 2-Butoxy ethyl acetate

Dipropylene glycol monomethyl ether acetate

Propylene glycol diacetate

Texanol

TXIB (Texanol isobutyrate)

Aldehydes (26)

Formaldehyde^{*} Acetaldehvde^{1,3,4} Propanal^{1,3} Butanal^{1,3} 3-Methyl-1-butanal Pentanal Hexanal 2-Ethylhexanal Heptanal Octanal Nonanal Decanal

Propenal (Acrolein)1 Isobutenal (Methacrolein)³ 2-Butenal

2-Pentenal³ 2-Hexenal 2-Heptenal 2-Octenal



2-Nonenal 2-Decenal 2-Undecenal

Ethanedial (Glyoxal)^{1,3}

Glutaraldehyde Furfural Benzaldehyde

Ketones (15)

Acetone^{1,2} 1-Hydroxyacetone Ethylmethylketone³ Methylisobutylketone 3-Methyl-2-butanone Cyclopentanone

2-Methylcyclopentanone

Cyclohexanone

2-Methylcyclohexanone

2-Hexanone 2-Heptanone Acetophenone Isophorone Benzophenone⁴

4-Methylbenzophenone²

Acids (11)

Acetic acid Propionic acid Pivalic acid Butyric acid Isobutyric acid n-Valeric acid n-Caproic acid 2-Ethylhexanoic acid n-Heptanoic acid n-Octanoic acid Neodecanoic acid

Esters and Lactones (33)

Methyl acetate1 Ethyl acetate¹ Vinyl acetate¹ Propyl acetate Isopropyl acetate

2-Methoxy-1-methylethyl acetate

n-Butyl acetate Isobutylacetate 2-Ethylhexyl acetate n-Butyl formate

Methyl acrylate Methyl methacrylate Butyl methacrylate Ethyl acrylate n-Butyl acrylate

2-Ethylhexyl acrylate 2-Ethylhexyl methacrylate Hexanediol diacrylate

Dipropylene glycol diacrylate

Dimethyl succinate Dimethyl glutarate Dimethyl adipate Dibutyl fumarate Dibutyl maleate Diisobutyl succinate Diisobutyl glutarate Butyrolactone Dimethyl phthalate Diethyl phthalate² Dipropyl phthalate² Dibutyl phthalate² Diisobutyl phthalate²

(5-Ethyl-1,3-dioxan-5-yl)methyl acrylate

Chlorinated hydrocarbons (18)

Dichloromethane¹

Trichloromethane (Chloroform)⁴

Tetrachloromethane 1,2-Dichloroethane 1,1,1-Trichloroethane 2-Chloropropane 1,2,3-Trichloropropane4 Trichloroethene4 Tetrachloroethene trans-1,3-Dichloropropene4 cis-1,3-Dichloropropene4

Chloroprene4 1,3-Dichloro-2-propanol4 Chlorobenzene 1,4-Dichlorobenzene alpha-Chlorotoluene

alpha,alpha,Trichlorotoluene4

1,1-Dichlorethene1

Cyclic siloxanes (5)

Hexamethylcyclotrisiloxane (D3) Octamethylcyclotetrasiloxane (D4) Decamethylcyclopentasiloxane (D5) Dodecamethylcyclohexasiloxane (D6) Tetradecamethylcycoheptasiloxane (D7) Others (42)

1,4-Dioxane4

1,2-Dibromoethane4

2-Nitropropane4

2,3-Dinitrotoluene4

2 4-Dinitrotoluene

2,6-Dinitrotoluene4 3,4-Dinitrotoluene^{2,4}

o-Anisidine4

o-Toluidine4

4-Chloro-o-toluidine4

5-Nitro-o-toluidine²

Acrylonitrile1,4

2,2'-Azobisisobutyronitrile Tetramethylsuccinonitrile

Azobenzene^{2,4}

Caprolactam Furan1,4 2-Methylfuran 2-Pentylfuran Methenamine Triethylamine 2-Butanonoxime4

Triethyl phosphate Tributyl phosphate²

5-Chloro-2-methyl-4-isothiazolin-3-one (CIT)

2-Methyl-4-isothiazolin-3-one (MIT) 2-n-Octyl-4-isothiazolin-3-one (OIT)

Formamide

Dimethylformamide (DMF)

Acetamide

N-Nitrosopyrrolidine4 N-Methyl-2-pyrrolidone N-Ethyl-2-pyrrolidone N-Butyl-2-pyrrolidone

Aniline⁵ 4-Chloroaniline4 2-Nitroanisole4 Cyclohexyl isocyanate p-Cresidine4 Diethyl sulfate⁴

Epichlorohydrin4 5-Ethyl-1,3-dioxan-5-methanol

VVOC 1

2 SVOC

Analysis acc. to DIN ISO 16000-3:2023-12 (DNPH) 3

Carcinogens, category 1A and 1B according to Regulation (EC) No 1272/2008 and TRGS 905

When analysing with TD-GC-MS, aniline can occur as a thermal decomposition product of other substances (e.g. 1.3-Diphenylquanidine). A cold analytical method is recommended to confirm the result.

(Status: August 2024)



Definition of terms

CAS No. (Chemical Abstracts Service)

CMR

Limit of quantification (LOQ)

NIK / LCI

RT (retention time)

R value

R value according to AgBB

R-value according to Belgian regulation

R value according to eco-INSTITUT-Label

R value according to EU-LCI

SER

SVOC (semi volatile organic compound)

Toluene equivalent

TSVOC

TSVOC according to DIN EN 16516

TSVOC with LCI according to AgBB

TSVOC with LCI according to eco-INSTITUT-Label

TSVOC without LCI according to AgBB

TSVOC without LCI according to eco-INSTITUT label

TVOC

International designation standard for chemical substances

VOCs, VVOCs and SVOCs classified as carcinogenic, mutagenic or toxic for reproduction according to Regulation (EC) No. 1272/2008, TRGS 905, IARC list and DFG (MAK list)

Lower limit of quantification in the analytical method within the defined measurement uncertainty

Lowest concentration of interest; substance-specific value for health assessment of emissions from products, indicated in $\mu g/m^3$

Total time required for an analyte to pass the column (time between injection and detection of the analyte)

Sum of quotients of concentration and LCI value for all substances for which a LCI value is derived

R-value for all substances \geq 5 $\mu g/m^3$ with LCI value, calculated according to the LCI list of the AgBB scheme

R-value for all substances $\geq 5~\mu g/m^3$ with LCI-value, calculated according to the LCI-list of the Belgian regulation

R-value for all substances $\geq 1~\mu g/m^3$ with LCI value, calculated according to the LCI list of the AqBB scheme

R-value for all substances \geq 5 $\mu g/m^3$ with EU-LCI value, calculated according to the EU-LCI list of the European Commission

Specific emission rate (see "Explanation of Specific Emission Rate SER")

Organic compound eluting in the retention range > C_{16} (n-hexadecane) to C_{22} (docosane)

Concentration of a substance quantified by the TIC response factor of toluene (calculation of the concentration by comparing the integral of the substance with the integral of toluene)

Sum of the concentrations of all identified and unidentified semi volatile organic compounds eluting in the retention range $> C_{16}$ (n-hexadecane) to C_{22} (docosane)

Sum of all SVOC \geq 5 µg/m³ (as toluene equivalent)

Sum of all SVOC with LCI $\geq 5 \mu g/m^3$ (quantified substance-specific)

Sum of all SVOC with LCI $\geq 1 \mu g/m^3$ (quantified substance-specific)

Sum of all SVOC without LCI \geq 5 µg/m³ (as toluene equivalent)

Sum of all calibrated SVOC without LCI \geq 1 $\mu g/m^3$ (quantified substance-specific) and all non-calibrated SVOC without LCI \geq 1 $\mu g/m^3$ (as toluene equivalent)

Sum of the concentrations of all identified and unidentified volatile organic compounds eluting in the retention range from C_6 (n-hexane) to C_{16} (n-hexadecane)



TVOC according to DIN EN 16516

TVOC according to AgBB

TVOC according to eco-INSTITUT-Label

TVOC according to ISO 16000-6

TVOC without LCI according to AgBB

TVOC without LCI according to eco-INSTITUT-Label

TVVOC

TVVOC according to AgBB

TVVOC according to eco-INSTITUT-Label

VOC (volatile organic compound)

VVOC (very volatile organic compound)

Sum of all $VOC \ge 5 \ \mu g/m^3$ in the retention range C_6 to C_{16} , calculated as toluene equivalent (used i.a. for M1)

Sum of all VOCs with LCI $\geq 5~\mu g/m^3$ (quantified substance-specific) and all VOCs without LCI $\geq 5~\mu g/m^3$ (as toluene equivalent) (used i.a. for the Blue Angel)

Sum of all calibrated VOC \geq 1 $\mu g/m^3$ (quantified substance-specific) and all non-calibrated VOC \geq 1 $\mu g/m^3$ (as toluene equivalent) (used i.a. for natureplus)

Total area of the chromatogram in the retention range C_6 – C_{16} as toluene equivalent according to DIN ISO 16000-6, Annex A.1 item 3 (used i.a. for CDPH, BIFMA and the French VOC regulation)

Sum of all VOCs without LCI \geq 5 µg/m³ as toluene equivalent

Sum of all calibrated VOCs without LCI \geq 1 $\mu g/m^3$ (quantified substance-specific) and all non-calibrated VOCs without LCI \geq 1 $\mu g/m^3$ (as toluene equivalent)

Sum of the concentrations of all identified and unidentified very volatile organic compounds eluting in the retention range $< C_6$ (n-hexane)

Sum of all VVOC with LCI \geq 5 $\mu g/m^3$ (quantified substance-specificic) and all VVOC without LCI \geq 5 $\mu g/m^3$ (as toluene equivalent)

Sum of all calibrated VVOC \geq 1 $\mu g/m^3$ (substance-specific quantified) and all non-calibrated VVOC \geq 1 $\mu g/m^3$ (as toluene equivalent)

Organic compound eluting in the retention range from C_6 (n-hexane) to C_{16} (n-hexadecane)

Organic compound eluting in the retention range $< C_6$ (n-hexane)



Commentary on emission analysis

Test method

Measurement of the volatile organic compounds takes place in the test chamber in conditions similar to those applying in practice. Standardised test conditions are defined for the test chamber regarding loading, air exchange, relative humidity, temperature, and incoming air, based on the type of test specimen and the required guideline. These conditions and the underlying standards are to be found in the section on test methods in the laboratory report.

Air samples are taken from the test chamber at defined points in time during the continuously running test. To this end, approximately 5 L of air are collected from the test chamber at an air flow rate of 100 mL/min on Tenax and approx. 100 L at an air flow rate of 0.8 L/min on silica gel coated with DNPH (2,4-dinitrophenylhydrazine).

After thermal desorption, the substances adsorbed on Tenax are analysed using gas chromatographic separation and mass spectrometric determination. The gas chromatographic separation is performed with a slightly polar capillary column of 60 m in length.

The substances derivatised with DNPH for the determination of formaldehyde and other short-chain carbonyl compounds ($C_1 - C_6$) are analysed using high-performance liquid chromatography (HPLC).

Over 200 compounds, including volatile organic compounds ($C_6 - C_{16}$), semi-volatile organic compounds ($C_{16} - C_{22}$) and – insofar as possible with this method – also very volatile organic compounds (less than C_6) are determined and quantified individually.

All other substances – insofar as possible – are identified through comparison with a library of spectra. The quantification of these substances and non-identified substances is performed through a comparison of their signal area with the signal of toluene.

The determined substance concentrations are corrected using the recovery rate of the internal standard (toluene-d8). Identification and quantification of substances is carried out from a concentration (limit of quantification) of 1 μ g per m³ test chamber air or 2 μ g/m³ for DNPH-derivatised substances. In the case of highly loaded samples, the evaluation limit of non-calibrated substances is raised in some cases, as it is no longer possible to assign individual, small signals due to the large number of signals.

Quality assurance

The eco-INSTITUT Germany GmbH is granted flexible scope of accreditation pursuant to DIN EN ISO/IEC 17025:2018-03. The accreditation covers the analytical determination of all volatile organic compounds, including the test chamber method.

In each analysis the analytical system is checked using an external standard based on the specifications in standard DIN EN 16516:2020-10. The stability of the analytical systems is documented based on the test standard using control charts.

Laboratory performance is assessed at least once a year in inter-laboratory comparisons by comparing the results with those obtained by other laboratories for identical samples.

A blank is run prior to introducing the test specimen into the test chamber to check for the possible presence of volatile organic compounds.

The expanded measurement uncertainty U for the analytical determination of all volatile organic compounds, including the test chamber method, is estimated to 41.7 %. The calculation is based on DIN ISO 11352:2013-03 (Nordtest).



Explanation of Specific Emission Rate SER

Emission measurements are accomplished in test chambers under defined physical conditions (temperature, relative humidity, room loading, air change rate etc.).

Test chamber measurement results are directly comparable only if the investigations were accomplished under the same basic conditions.

If the differences of the physical conditions refer only to the change of air rate and/or the loading, the "SER" or "specific emission rate" can be used for comparability of the measurement results. The SER indicates how many volatile organic compounds (VOC) are released by the sample for each material unit and hour (h).

The SER can be calculated using the formula below for each proven individual component of the VOC from the data in the test report.

As material units the following are applicable:

I = unit of length (m) relation between emission and length
a = unit area (m²) relation between emission and surface
v = unit volume (m³) relation between emission and volume

u = piece unit (unit = piece) relation between emission and complete unit

From this the different dimensions for SER result:

 $\begin{array}{lll} \mbox{length-specific} & \mbox{SER}_l & \mbox{in } \mu g/(m \cdot h) \\ \mbox{surface-specific} & \mbox{SER}_a & \mbox{in } \mu g/(m^2 \cdot h) \\ \mbox{volume-specific} & \mbox{SER}_v & \mbox{in } \mu g/(m^3 \cdot h) \\ \mbox{unit-specific} & \mbox{SER}_u & \mbox{in } \mu g/(u \cdot h) \end{array}$

SER thus represents a product specific rate, which describes the mass of the volatile organic compound, which is emitted by the product per time unit at a certain time after beginning of the examination.

$$SER = q \cdot c$$

- q specific air flow rate (quotient from change of air rate and loading)
- c concentration of the measured substance(s)

The result can be indicated in milligrams (mg) in place of micro grams (μ g), whereby 1 mg = 1000 μ g.