

REALLY KNOWS WHAT IT'S DOING



Wood protection outdoors & indoors

PRODUCT CATALOGUE





A future-oriented family business since 1934



Austria's leading manufacturer of paints, varnishes and wood preservatives



Sole production site in Schwaz, Austria



Annual production 21,000 tonnes



Europe's most advanced water-based coatings factory



730 employees, including 120 in Research & Development



Environmentally friendly products, 65 % water-based paints



100 % climate-neutral production¹







ADLER does not merely pay lip service to quality, responsible action and social commitment. As is proven by numerous awards and certifications, for which the paint factory regularly undergoes strict inspections.



More information: www.adler-coatings.com/climate-neutral

ADLER has been able to reduce its carbon footprint to a minimum through a wide range of measures. ADLER offsets any unavoidable residual emissions through the purchase of recognised climate protection certificates, thereby helping to finance new climate protection projects.

CONTENTS

WOOD PROTECTION		OPAQUE	
Areas of application	6	Pullex Color	24
Material: wood	6	Pullex 2in1 Top-Color	24
Wood protection in outdoor areas	7	Pullex Aqua-Color	25
Coating cycle recommendations	8		
		OILS	
PRE-TREATMENT &		Pullex Holzöl	26
ADDITIVES		Pullex Bodenöl	26
WurmEx	11	Pullex Teaköl	27
Clean-Multi-Refresher	11	Pullex Aqua-Terra	27
Abbeizer Spray	12		
Abbeizer Express	12	INDOOR AREAS	
Aviva Fungisan	13	Innenlasur	28
Alkydharzturbo	13	Innenlasur UV 100	28
Adlerol Terpentinölersatz	14	Terra Wax-Oil	30
Feinspachtel	14	Legno-Öl	30
		Legno Dura-Öl	31
PRIMERS		Legno-Zirbenöl	31
Pullex Imprägnier-Grund	16	Legno-Color	32
Pullex Renovier-Grund	16	Legno-Hartwachsöl	33
Pullex Aqua-IG	17	Legno-Wachs	33
CLATEC		Legno-Reiniger und -Pflegeöl	34
GLAZES		Legno-Pflegeset	34
Pullex 2in1-Holzlasur	18	Legno-Holzbodenseife	35
Pullex 3in1-Lasur	18	Windoor-Care-Set	35
Pullex Plus-Lasur	19		
Pullex Top-Lasur	20	PRODUCT OVERVIEW	37
Pullex Top-Mattlasur	20		
Pullex Fenster-Lasur	21	WORKING EQUIPMENT	
Protector Plus	21	Solvamaxx Plus	38
Pullex Silverwood	22	Aquamaxx Plus	38
Pullex Platin	22	Brush for applying glaze HS 50	38
Pullex Aqua 3in1-Lasur	23	Brush for applying oils to floor surfaces	38
Pullex Aqua-DSL	23	Brush for staining and dusting off	39
		Brass-wire brush	39
		Brass-wire brush with strap	39
		Paint scraper	39

WOOD PROTECTION EXPERTISE

The research and development of wood protection coatings began decades ago at the ADLER plant. These products underwent continuous improvement as the years went by. ADLER's Pullex wood protection range offers unique impregnations, glazes, opaque paints and wood oils which, thanks to the use of state-of-the-art technologies, ensure extremely good long-term durability. This is why more and more professionals swear by the top brand quality of Austria's number 1. This gives you the security to offer your customers the best.





Under the green sustainability label, you will find the most sustainable coatings in ADLER's product range. In doing so, ADLER relies on the UN's Sustainable Development Goals, which ADLER has defined as the basis for its responsible actions. All products are objectively tested and certified according to three categories: Environment, Health & Safety and Service life. Only products that score positively in all these areas are awarded the green sustainability label.





Environment

high percentage of renewable raw materials

low carbon footprint

without the addition of substances that are damaging to the environment

low VOC content



Health & Safety

without the addition of allergens or substances that are hazardous to health

use of the products does not present any health risk



Service life

long shelf life highly durable good colour stability

WOOD PROTECTION

AREAS OF APPLICATION



Wooden structures that are not dimensionally stable

These include fences, formwork, roof trusses and wooden structures as well as balconies and garden furniture. The term "not dimensionally stable" refers to wood that can swell and shrink. The coating should be designed for this change.



Limited dimensionally stable wooden structures

Window shutters, conservatory structures and garages as well as entrance gates are specially manufactured here as end products. A good choice of wood is necessary, as wooden structures are made which can only compensate for slight swelling and shrinkage.



Dimensionally stable wooden structures

For windows and doors, swelling or shrinkage cannot be accepted. Very high wood quality is required. On the one hand, deformations can cause problems when opening windows and doors. On the other hand, fine hairline cracks occur during the final coating, which inevitably lead to damage to the coating.

MATERIAL: WOOD

Differences between softwoods and hardwoods



Softwood

Spruce, pine, larch etc. are inexpensive and well suited for timber construction.

The higher the resin content in the wood, the more resistant the wood is to pests. However, a high resin content is disadvantageous for the penetration of the coating into the wood. Particularly in the case of larch and pine, shortened durability of the coating and flow of resin can therefore be expected. These resinous woods should be removed of resin before coating with ADLER Aceton-Waschmittel 95130. Resinous woods should not be coated dark. Increased flow of resin may occur due to the increased heating of dark colours.



Hardwood

Hardwoods suitable for outdoor use such as oak, acacia, chestnut and various exotic woods (teak, mahogany, meranti ...) are very durable. Due to the porosity of some woods, poor wetting may occur in the area of the pores. An improvement in pore wetting can be achieved by wiping out the first coat with a cloth.

Nevertheless, a shortened maintenance interval can be expected here as well. In many cases, exotic woods contain substances that may impair the drying of the coating. It should also be noted that substances in the wood can cause washing out and discolouration.



WOOD PROTECTION IN OUTDOOR AREAS

Long-term protection through the combination of structural and chemical wood protection



Structural protection

Structural protection is the responsibility of the designer and can, as far as possible, prevent the wooden structure from coming into direct contact with water, e.g. through the eaves. An angle of inclination of at least 5° is in any case important for all horizontal wooden surfaces exposed to rain, as is the use of suitable materials. Even the best wood protection cannot compensate for defects in the wooden structure in the long run!

- ✓ Avoid contact of the wood with ground (min. 30 cm)
- ✓ Protect cross-cut wood
- ✓ Use wood material suitable for use in outdoor areas
- ✓ Ensure the fastest possible water drainage

Physical wood protection

Physical protection is achieved by using varnishes and glazes that counteract the degradation of the wood in outdoor areas. ADLER is one of the largest European paint manufacturers for wood coatings. The high quality of ADLER products guarantees optimal protection of the wood, which counteracts the most significant decomposition factors.

Chemical wood protection

ADLER impregnations are certified according to EN 113 against rot fungi, EN 152 against blue stain fungi and EN 46 against insects. This gives the consumer certainty regarding the actual quality and effectiveness of the products purchased. It goes without saying that the effectiveness of and compliance with the above-mentioned standards is also monitored externally. Only wood preservatives controlled in this way are included in the Austrian Wood Preservatives Register (www. holzschutzmittel.at).



UV protection

Wood needs sufficient protection against UV radiation. This UV protection protects the wood structure from decomposition (lignin degradation).

Strongly pigmented paints offer the best protection. The pigments ensure that the radiation is reflected as fully as possible.

Colourless systems with UV protection can only provide sufficient protection for a relatively short period of time and must be maintained at short intervals (approx. every 2 years).

Less resistant new woods (pine, spruce, etc.) in outdoor areas must be pre-treated with a preservative impregnation for wood before coating. This is the only way to ensure sufficient wood protection. The impregnation is carried out once by means of the painting method (water- or solvent-based according to the subsequent glaze coating).

RECOMMENDED COATING SYSTEMS

FIRST-TIME COATING

ADLER wood preservers reliably protect and upgrade wood as a working material. They are carefully tested and therefore generally recognized as safe for our health. With their broad range of water-thinnable and solvent-based wood finishing products, ADLER has been offering top-class solutions for all areas of use for many decades now.

OPAQUE



Impregnation	Primer coat	1. Top coat	2. Top coat
Pullex Imprägnier-Grund ¹		Pullex Color	Pullex Color
		Pullex 2in1 Top-Color	Pullex 2in1 Top-Color
Pullex Aqua-IG ¹	Aqua-Isoprimer PRO (for white and lighter pastel shades)	Pullex Aqua-Color	Pullex Aqua-Color

TRANSPARENT



Impregnation (if required)	1. coat	2. coat
	Pullex 2in1-Holzlasur	Pullex 2in1-Holzlasur
Pullex 3in1-Lasur	Pullex 3in1-Lasur	Pullex 3in1-Lasur
Pullex Imprägnier-Grund ¹	Pullex Plus-Lasur	Pullex Plus-Lasur
Pullex Imprägnier-Grund ¹	Pullex Top-Lasur or Pullex Top-Mattlasur	Pullex Top-Lasur or Pullex Top-Mattlasur
Pullex Aqua 3in1-Lasur	Pullex Aqua 3in1-Lasur	Pullex Aqua 3in1-Lasur

Use wood preservatives carefully. Always read the label and the respective technical data sheets of the products before use, which can be found at www.adler-lacke.com.



RECOMMENDED COATING SYSTEMS

RENOVATION

With the Pullex renovation system, you can make weathered and unsightly cladding, balconies or canopies look like new again in just a few steps. Simply brush, prime, glaze and you're done!

OPAQUE



Primer coat	1. Top coat	2. Top coat
Pullex Renovier-Grund (roughly tinted to final colour)	Pullex Color	Pullex Color
Pullex Renovier-Grund (only necessary for Weathering Level 3)	Pullex 2in1 Top-Color	Pullex 2in1 Top-Color
Pullex Renovier-Grund (roughly tinted to final colour) (at least 48 hours drying between coats!)	Pullex Aqua-Color	Pullex Aqua-Color

TRANSPARENT



Primer coat	1. Top coat	2. Top coat
Pullex Renovier-Grund	Pullex Top-Lasur	Pullex Top-Lasur
(poss. "wet-on-wet")	or Pullex Top-Mattlasur	or Pullex Top-Mattlasur
Pullex Renovier-Grund (poss. "wet-on-wet")	Pullex Plus-Lasur	Pullex Plus-Lasur
None	Pullex Top-Lasur	Pullex Top-Lasur
(if substrate is well preserved)	or Pullex Top-Mattlasur	or Pullex Top-Mattlasur

When renovating wood, pore-deep cleaning is very important. To ensure that the new paint finish lasts, it is essential to remove loose parts and residues of old coats of paint from the weathered substrates.

RECOMMENDED COATING SYSTEMS

RENOVATING WINDOWS AND EXTERIOR DOORS

Softwoods and hardwoods

With Pullex Renovier-Grund, Pullex Color and Pullex Fenster-Lasur, ADLER offers a long-standing, tried and tested renovation system for weathered windows and doors with thin- and thick-coat glaze finish. With this system, windows, doors or window shutters will shine in new splendour again without much effort.

OPAQUE



Species of wood	Primer coat	1. Top coat	2. Top coat
Softwoods and hardwoods	Pullex Renovier-Grund	Pullex Color	Pullex Color
Softwoods and hardwoods	Pullex Renovier-Grund (only necessary for Weathering Level 3)	Pullex 2in1 Top-Color	Pullex 2in1 Top-Color

TRANSPARENT



Species of wood	Primer coat	1. Top coat	2. Top coat
Softwood	Pullex Renovier-Grund	Pullex Fenster-Lasur	Pullex Fenster-Lasur
Hardwood	Pullex 3in1-Lasur or alternatively Pullex Plus-Lasur (choice of colours)	Pullex Fenster-Lasur Colour "Natur für Laubholz" (Nature for hardwood)	Pullex Fenster-Lasur Colour "Natur für Laubholz" (Nature for hardwood)

When renovating wood, pore-deep cleaning is very important. To ensure that the new coat of paint or varnish lasts, it is essential to remove loose debris and residues of old coatings from the weathered substrate.

PRE-TREATMENT & ADDITIVES





WurmEx

For the control and prevention of wood pests

- To control wood-destroying insects (controlling effect through application of approx. 300 ml/m²) in indoor and outdoor areas.
- Preventive measure against insect infestation through application of approx. 200 ml/m².
- Water-based and therefore odourless

AREAS OF APPLICATION

ADLER WurmEx is suitable for all types of wood that require preventive treatment against or control of insect infestation, such as roof trusses, stairs or furniture. Wooden objects intended for the storage of food or animal feed may not be treated with ADLER WurmEx and the same applies to beehives.

METHOD OF APPLICATION

Paintbrush, dip-coating or drill-hole impregnation. 2 – 3 applications are required to introduce the required amount of active ingredient into the wood.

CONSUMPTION approx. 100 ml/m² when applied by paintbrush **CONTAINER SIZES** 125 ml, 750 ml, 2.5 l **PRODUCT NUMBER** 8305000200

























Clean-Multi-Refresher

For cleaning and freshening up wood, plastic and masonry

- For cleaning and freshening up weathered and greying wooden terraces, garden furniture, plastic and masonry.
- Removes dirt, moss and decomposed substances on wood.
- Removes grey areas and brightens up wooden surfaces, giving them back their original colour.
- Easy to apply with a paintbrush, scrubbing brush or spray bottle, can also be used on vertical surfaces.
- Biodegradable.

AREAS OF APPLICATION

For cleaning, de-greying and freshening up greying wood (e.g. garden furniture, terraces, plastic and masonry)

METHOD OF APPLICATION paintbrush, scrubbing brush, spray bottle CONSUMPTION approx. 5 m²/l undiluted 500 ml (spray bottle), 1 l, 2,5 l **CONTAINER SIZES** PRODUCT NUMBER 8317000210



























PRE-TREATMENT & ADDITIVES







Abbeizer Spray

For the removal of old window coating systems and layers of paint or varnish

- Easy to use
- Also ideally suited to use on vertical surfaces thanks to its gel consistency
- Without the addition of chlorinated hydrocarbons

AREAS OF APPLICATION

Particularly suitable for removing old, water-based window coating systems and for small-scale items such as wooden windows, exterior doors, furniture, railings, frames, fittings, etc. Also effective with many 2C systems. (conduct preliminary test)

METHOD OF APPLICATION

Spray on liberally and let the product work in for about 10 minutes. Then use an ADLER paint scraper blade to remove the old coating, which will now have swollen up.

CONSUMPTION $2 - 3 \text{ m}^2/1$ **CONTAINER SIZES** 400 ml PRODUCT NUMBER 831108096937























ABBEIZER EXPRESS

Highly effective paint stripper with gel consistency

- Fast and easy to use
- Also suitable for vertical surfaces due to its gel consistency
- Removes thick layers of paint or varnish in a single step
- Without the addition of chlorinated hydrocarbons

AREAS OF APPLICATION

Particularly suited to the removal of old, water-based window frame coatings, ideal for vertical surfaces such as wooden windows, exterior doors, furniture, railings, frames, fittings, etc.

METHOD OF APPLICATION

Apply a liberal coating of Abbeizer Express and then leave for approx. 10 minutes to soak in. Use an ADLER paint scraper blade or paint scraper to remove the old coating, which will now have swollen up.

CONSUMPTION approx. $4 - 5 \text{ m}^2/1$ **CONTAINER SIZES** 500 ml

PRODUCT NUMBER 831300030012



























Aviva Fungisan

Disinfection solution for the restoration of surfaces infested by fungi, algae and green growth

- Water-based and therefore low-odour
- Without the addition of heavy metals and phenolic compounds
- · Intact coatings are not affected

AREAS OF APPLICATION

Masonry or wood that has become infested by mould, algae or green growth.

METHOD OF APPLICATION Apply with a paintbrush or scrubbing brush CONSUMPTION approx. 8 m²/l

CONTAINER SIZES 11,51 **PRODUCT NUMBER** 8308000210






















Alkydharzturbo

Hardener for synthetic resin systems and oils to improve drying and durability

- For transparent and opaque synthetic resin systems and oils
- To improve mechanical and chemical resistance and speed up drying in unfavourable climatic conditions (temperature, humidity)
- Also suitable for woods rich in active substances

AREAS OF APPLICATION

Suitable as hardener component for solvent-based synthetic resin coatings (e.g. ADLER Express-Maschinenlack, Samtalkyd, Brilliantalkyd, Ferro GSX), solventbased Pullex products (e.g. Pullex Color, Pullex Renovier-Grund, Pullex Plus-Lasur, Pullex Top-Lasur/Pullex Top-Mattlasur, Pullex High-Tech) and Legno oils.

Add Alkydharzturbo to the paint/varnish component and mix in carefully.

CONTAINER SIZES 250 ml, 1 l **PRODUCT NUMBER** 8054000210

PRE-TREATMENT & ADDITIVES



Adlerol-Terpentinölersatz

Cleaner and paint thinner for synthetic resin coatings

- Free from aromatic hydrocarbons
- Suitable for universal use

AREAS OF APPLICATION

Adlerol is a high-quality cleaner for paintbrushes and painting equipment. It is also ideally suited for use as a paint thinner for synthetic coatings (e.g. ADLER Express-Maschinenlack, Samtalkyd, Brillantalkyd, Allwetterlack) and allows you to adjust the viscosity of the coating to the optimum level.

HOW TO USE

To use as a thinner, add Adlerol to the synthetic resin paint or varnish and mix in carefully.

CONTAINER SIZES 500 ml, 1 l, 5 l, 25 l 8002000210



Fine putty

Water-based fine putty

- Water-thinnable putty filler made from an acrylate dispersion
- Fills well, fast drying, high yield
- Low in harmful substances

AREAS OF APPLICATION

For filling cracks, holes or small surfaces in both interior and exterior settings.

HOW TO USE

Apply with a rust-free metal spatula or a plastic spatula, the product can be applied several times in a day, wet on wet.

CONTAINER SIZES 400 g, 1300 g **PRODUCT NUMBER** 7525040364



PRIMERS



Standard colour Colourless 4436000200

Pullex Imprägnier-Grund

System impregnation primer for solvent-based **ADLER wood coatings in outdoor areas**

- Solvent-based protective wood impregnation treatment, free from aromatic hydrocarbons.
- Tested and monitored wood preserver.
- The active substances used offer protection against blue stain (testing in accordance with EN 152-1) and wood-destroying fungi (testing in accordance with EN 113) as required by ÖNORM B 3802-2 and DIN 68800-3 and also prevent insect infestation (testing in accordance with EN 46). Quantity to apply for standard test approx. 150 q/m² (Certificate of Approval No. 6/93).

AREAS OF APPLICATION

Wooden houses, canopies, wooden cladding, balconies, roof trusses, windows and exterior doors, etc. in usage classes 2 and 3.

METHOD OF APPLICATION

Paintbrush, short dip-coating, flow coating.

Do not spray on!

CONSUMPTION **CONTAINER SIZES** $8 - 12 \text{ m}^2/\text{l}$ 750 ml, 2.5 l, 5 l, 20 l

























Standard colours 4416057113 4416057101

Base for tinting 50256

Color4You

Pullex Renovier-Grund

Semi-opaque, wood-strengthening, brightening primer

- Renovation primer suitable for universal use, semi-opaque and free from aromatic hydrocarbons.
- Has an equalising effect and brightens up the wood substrate.
- Covers spots and signs of greying.
- Perfect substrate preparation for subsequent Pullex wood coatings.
- The coating is protected against infestation by blue stain fungi and mould.

AREAS OF APPLICATION

Renovation of severely weathered, absorbent wooden structural elements, e.g. wooden houses, canopies, wooden cladding, balconies, windows, window shutters and gates.

METHOD OF APPLICATION CONSUMPTION **CONTAINER SIZES**

Paintbrush, do not spray on! $8 - 12 \text{ m}^2/1$ 750 ml, 2.5 l, 5 l, 10 l





















Use wood preservers with care. Always read the label and the relevant technical data sheets for the products before use. Technical data sheets can be found at www.adler-lacke.com.





Standard colour Colourless 5357000200

Pullex Aqua-IG

Water-based system impregnation primer

- System impregnation primer for water-based ADLER wood coatings, made from a special alkyd/acrylic dispersion, for use in outdoor areas.
- Prevents fungal and insect infestation.
- Tested and monitored wood preserver.
- The active substances used offer protection against blue stain (testing in accordance with EN 152-1) and wood-destroying fungi (testing in accordance with EN 113) as required by ÖNORM B 3802-2 and DIN 68800-3 and also prevent insect infestation (testing in accordance with EN 46). Quantity to apply for standard test approx. 100-120 g/m² (Certificate of Approval No. 10/91).

AREAS OF APPLICATION

Windows, doors, wooden cladding, canopies, balconies, roof trusses, etc. in usage classes 2 and 3.

METHOD OF APPLICATION

Paintbrush (acrylic brush), short dip-coating

and flow coating. Do not spray on!

CONSUMPTION **CONTAINER SIZES** $8 - 12 \text{ m}^2/\text{l}$ 750 ml, 2.5 l



























Pullex Renovier-Grund



Standard colours	
Oak	4477050044
Larch	4477050045
Pine	4477050046
Nut	4477050049
Palisander	4477050050
Colourless for brightening up	4477000200

Pullex 2in1-Holzlasur

Matt impregnation treatment and weather protection, all in one

- Solvent-based glaze, free from aromatic hydrocarbons, suitable for large areas
- Good protection against UV light and weather and excellent colour stability
- Suitable for universal use and easy to apply.
- · The coating is protected against blue stain fungi and mould thanks to a biocidal active ingredient.
- Very good water protection with excellent durability.
- Uniform degradation when exposed to weathering.

AREAS OF APPLICATION

Timber components in outdoor areas that are not dimensionally stable, e.g. wooden houses, canopies, wooden cladding, etc. Especially suitable for roof trusses, fences and agricultural buildings.

METHOD OF APPLICATION CONSUMPTION **CONTAINER SIZES**

Paintbrush, do not spray on! $8 - 12 \text{ m}^2/1$ 750 ml, 2.5 L, 5 L





















Standard colours 4465050044 Oak 4465050045 Larch Pine 4465050046 4465050049 Nut Palisander 4465050050

Base for tinting	
W30	4465000030

Color4You

Pullex 3in1-Lasur

Matt, oily wood glaze with film protection

- Solvent-based wood glaze suitable for universal use, for wood in outdoor areas.
- Impregnation, primer and final coat all in one, for first-time coating as well as maintenance coating.
- Gives the coated timber a matt, natural-looking surface.
- High-quality UV filters quarantee long-term protection against weathering.
- The coating penetrates deep into the wood, is water-repellent and regulates and protects against moisture.
- Coating protects against blue stain, mould and algae.

AREAS OF APPLICATION

Wooden structural elements in outdoor areas (preferably for components that are not dimensionally stable) such as wooden houses and log cabins, canopies, roofing underlayment, gables, wooden facades and cladding, balconies, shingles, wooden floors, garden furniture, pavilions, fences, etc.

METHOD OF APPLICATION CONSUMPTION **CONTAINER SIZES**

Paintbrush, do not spray on!

 $8 - 12 \text{ m}^2/\text{l}$

Standard colours: 750 ml, 2.5l, 5 l, 20 l W30: 750 ml, 2.5 l, 4.5 l, 9.5 l





















Standard colours		
Willow	4415050043	
Oak	4415050044	
Larch	4415050045	
Pine	4415050046	
Chestnut	4415050047	
Sipo	4415050048	
Nut	4415050049	
Palisander	4415050050	
Afzelia	4415050051	
Wenge	4415050052	
Chalk-white	4415067081	

Base for tinting

Color4You

W30

Pullex Plus-Lasur

Universal, open-pore, thin-film glaze finish

- Solvent-based wood glaze, free from aromatic hydrocarbons, or wood in outdoor areas.
- The coating is protected against infestation by blue stain fungi and mould.
- The combination of binding agents used, a high solids content and active UV filters quarantee long-term weather protection.
- No peeling.

AREAS OF APPLICATION

Wooden structural elements in outdoor areas that have no or only limited dimensional stability, such as wooden houses, canopies, wooden cladding and balconies. On deep-pored hardwoods, e.g. oak, maintenance is likely to be required at shorter intervals. When used on exotic woods (like iroko) the drying process may be delayed.

METHOD OF APPLICATION CONSUMPTION CONTAINER SIZES

Paintbrush, do not spray on!

 $8 - 12 \text{ m}^2/\text{l}$

Standard colours: 125 ml, 750 ml, 2.5 l, 5 l, 20 l

W30: 750 ml, 2.5 l, 4.5 l, 10 l






















STANDARD COLOURS

50410



Weide



Eiche



Lärche



Kiefer



Kastanie



Sipo



Nuss



Palisander



Afzelia



Wenge



Standard colours		
Willow	4421050043	
Oak	4421050044	
Larch	4421050045	
Pine	4421050046	
Chestnut	4421050047	
Sipo	4421050048	
Nut	4421050049	
Palisander	4421050050	
Afzelia	4421050051	
Wenge	4421050052	
Chalk-white	4421067081	

Base for tinting	
W30	50550

Color4You

Pullex Top-Lasur

Drip-inhibited thin-film glaze finish for first-time coating and renovation - especially for trade

- Solvent-based wood glaze with high solids content.
- The coating is protected against infestation by blue stain fungi and mould.
- Exceptionally easy to use, moisture-regulating, highly diffusible.
- Very good capacity to penetrate into the wooden substrate.
- Special light stabilisers quarantee long-term weather protection.
- Ideal system partner for renovation projects with Pullex Renovier-Grund.

AREAS OF APPLICATION

Wooden structural elements in outdoor areas that have no or only limited dimensional stability, such as wooden houses, canopies, wooden cladding, balconies, garden furniture, etc.

METHOD OF APPLICATION CONSUMPTION **CONTAINER SIZES**

Paintbrush, do not spray on! approx. $10 - 12 \text{ m}^2/\text{l}$

Standard colours: 750 ml, 2.5l, 5 l, 20 l W30: 750 ml, 2.5 l, 4.5 l, 9.5 l



















Base for tinting W30 4455000030

Color4You

Pullex Top-Mattlasur

Drip-inhibited, matt wood glaze with excellent weather protection

- Long-oil alkyd resins and a high solids content quarantee the best possible resistance to weathering
- Exceptionally easy to use on account of improved drip inhibition.
- Contemporary, dull matt surfaces.
- Thin-film glaze finish is protected against blue stain fungi and mould.
- Moisture-regulating, highly diffusible and highly water repellent.
- Very good capacity to penetrate into the wooden substrate.
- Special light stabilisers quarantee long-term weather protection.
- Ideal system partner for renovation projects with Pullex Renovier-Grund.

AREAS OF APPLICATION

Wooden structural elements in outdoor areas that have no or only limited dimensional stability, such as wooden houses and log cabins, gables, canopies, roofing underlayment, wooden facades and cladding, balconies, garden pavilions, etc.

METHOD OF APPLICATION CONSUMPTION **CONTAINER SIZES**

Paintbrush, do not spray on! $8 - 12 \text{ m}^2/1$ 750 ml, 2.5 l, 4.5 l, 9,5 l





















Base for tinting

W30

50413

Color4You

Pullex Fenster-Lasur

Renovation glaze for windows and doors

- Solvent-based wood glaze, free from aromatic hydrocarbons, especially suitable for a final coat in the renovation of windows and doors.
- Long-term protection against weathering thanks to special pigments and UV filters.
- Biocide-free system coating, for use with Pullex Renovier-Grund 50236 ff.
- Very fast drying, block-resistant.


AREAS OF APPLICATION

For the renovation of dimensionally stable components and components with limited dimensional stability, such as wooden windows, wooden doors, window shutters and gates.

METHOD OF APPLICATION Paintbrush $8 - 10 \text{ m}^2/l$ **CONSUMPTION CONTAINER SIZES** 750 ml, 2.5 l



















Protector Plus

Glaze with excellent hydrophobic properties

- Colourless glaze for industry and trade, for wood in outdoor areas.
- Highly-effective absorber of UV light.
- Very good hydrophobic properties, excellent capacity to penetrate the substrate.
- The coating is protected against infestation by blue stain fungi and mould.

AREAS OF APPLICATION

For wooden structural elements made of softwood in outdoor areas that are not dimensionally stable. Greying is significantly delayed, but not prevented in the long term.

METHOD OF APPLICATION

Dip-coating, paintbrush.

CONSUMPTION **CONTAINER SIZES** $8 - 10 \text{ m}^2/l$ 2.5 1, 20 1

PRODUCT NUMBER

440100020020



















Standard colours	
Altgrau	4464054364
Silber	4464057002
Graualuminium	4464066512
Fichte hell geflämmt	4464054776
Colourless for brightening up	4464000200



Pullex Silverwood

Special effect wood glaze with special pigmentation

- Solvent-based impregnation glaze, free from aromatic hydrocarbons, for textured softwoods in outdoor areas.
- Primer, intermediate coat and top coat, all in one.
- Special pigmentation results in a silvery patina effect when the surface is exposed to weathering.
- Innovative colours with metal effect or ageing wood character.
- The developing patina means that repainting is not necessary. No peeling

AREAS OF APPLICATION

Wooden structural elements in outdoor areas that are not dimensionally stable, e.g. wooden houses, canopies, wooden cladding, etc. For a pronounced rustic effect, we recommend using rough-sawn, brushed and chopped softwood.

METHOD OF APPLICATION CONSUMPTION

Paintbrush, do not spray on! approx. $4-12 \text{ m}^2/1$ (depending on the absorbency of the substrate) 750 ml, 5 l, 20 l





CONTAINER SIZES













Base for tinting W30 4447000030

Color4You

Pullex Platin

Metallic wood glaze

- Solvent-based, thin-layer, metallic wood glaze for wood in outdoor areas, free from aromatic hydrocarbons.
- Special pigmentation creates spectacular, shimmering metallic colour effects.
- This open-pored product gives very good weather protection, is highly durable and ensures uniform degradation when the surface is exposed to weathering.
- The coating is protected against infestation by blue stain fungi and mould.

AREAS OF APPLICATION

Wooden structural elements in outdoor areas that have no or only limited dimensional stability, e.g. wooden houses, canopies, wooden cladding, etc. For a pronounced metallic effect, we recommend using rough-sawn, brushed and chopped softwood.

METHOD OF APPLICATION CONSUMPTION **CONTAINER SIZES**

Paintbrush, do not spray on! $8-12 \text{ m}^2/\text{I}$ (depending on the absorbency of the substrate) 750 ml, 2.5 l





















Standard colours	
Oak	5368050044
Larch	5368050045
Pine	5368050046
Chestnut	5368050049
Palisander	5368050050

Base for tinting	
W30	5368000030

Color4You

Pullex Aqua 3in1-Lasur

Matt, water-based, protective wood impregnation glaze

- Impregnation, primer and final coat, all in one.
- For first-time coating and maintenance coating of wooden facades, balconies, etc.
- Very good resistance to weathering and UV protection.
- Gives the coated wood a matt surface.
- The coating is protected against infestation by blue stain fungi and mould.
- Water-based thin-film glaze finish no peeling when exposed to weathering.

AREAS OF APPLICATION

Wooden structural elements in outdoor areas that have no or only limited dimensional stability, e.g. wooden houses, canopies, wooden cladding, balconies, etc.

METHOD OF APPLICATION CONSUMPTION **CONTAINER SIZES**

Paintbrush (soft acrylic brush), do not spray on! $10 - 12 \text{ m}^2/1$

Standard colours: 750 ml, 2.5 l, 10 l

W30: 750 ml. 2.5 l. 9.5 l





















Standard colours 5338100845 Natur 5338053819 Base for tinting

51513

W30 Color4You

Pullex Aqua-DSL

Water-based thick-coat glaze finish for windows and doors

- Environmentally friendly wood glaze made from an acrylate dispersion with good resistance to weathering and UV light.
- Ideal product for the maintenance and renovation of window frames.
- Compatible with the colour ranges of all leading window manufacturers.
- Excellent permanent elasticity, outstanding transparency and block resistance.
- Biocide-free, breathable.

AREAS OF APPLICATION

Dimensionally stable wooden structural elements (windows and exterior doors) and load-bearing small-scale sections of conservatories.

METHOD OF APPLICATION Paintbrush **CONSUMPTION** $8 \, \text{m}^2 / 1$ **CONTAINER SIZES** 750 ml. 2.5 l

















OPAQUE



Standard colours	
W10 White	50530
Yellow	50532
Red	50533
Brown	50535
RAL 6005	4403006005

Base for tinting	
W20	50531
W30	50537

Color4You

Pullex Color

Opaque, breathable wood paint

- Solvent-based wood paint for use in exterior settings.
- Optimal weather protection for first-time coatings and renovation projects.
- Permeable and moisture-regulating.
- Opaque, lots of bright colours.
- The coating is protected against infestation by blue stain fungi and mould.

AREAS OF APPLICATION

For all dimensionally stable wooden structural elements, as well as those with limited or no dimensional stability; particularly suited to the renovation of weathered, oil-based opaque wood coatings.

METHOD OF APPLICATION

Paintbrush or roller

CONSUMPTION

 $10 \, \text{m}^2/\text{l}$

CONTAINER SIZES

Standard colours:750 ml, 2.5 l, 10 l

W20, W30: 750 ml, 2.5 l, 9.5 l (not available in all colours)























Standard colours	
W10 White	4430000010

Base for tinting W30 4430000030

Color4You

Pullex 2in1 Top-Color

Wood paint for efficient first-time coating or renovation projects

- Can be used for all renovation projects and first-time coats.
- · No additional primer needed.
- Easy to use with very little resistance when applied with a brush.
- Fast drying.
- · Silky matt surface.

AREAS OF APPLICATION

For wooden structural elements in outdoor areas that are dimensionally stable or not dimensionally stable, e.g. windows, doors, gates, wooden facades, canopies, balconies, fences, etc.

METHOD OF APPLICATION Paintbrush or roller CONSUMPTION $8 - 12 \text{ m}^2/\text{l}$ **CONTAINER SIZES** 750 ml, 2.5 l, 10 l





























Standard colours	
W10 White	53331
RAL 6005	5325006005

Base for tinting	
W20	53332
W30	53334
Y	53335
R	53336

Color4You

Pullex Aqua-Color

Opaque, water-based wood paint

- Water-thinnable, opaque wood paint made from acrylate and alkyd resin dispersions, particularly suitable for first-time coatings.
- Extremely weather resistant and excellent colour stability.
- The coating is protected against infestation by blue stain fungi and mould.
- Unlimited variety of colours.

AREAS OF APPLICATION

Wooden structural elements that have no or only limited dimensional stability, e.g. wooden facades, canopies, balconies, etc.

METHOD OF APPLICATION CONSUMPTION **CONTAINER SIZES**

Paintbrush (acrylic brush) $8 - 10 \text{ m}^2/\text{l}$ 750 ml, 2.5 l, 10 l



















Pullex 2in1 Top-Color



Standard colours	
Colourless	50520
Larch	4410050045
Nature	4410085820



Pullex Holzöl

Wood oil made from natural, refined oils

- Oil that is rich in binding agents, for vertical wooden surfaces in outdoor areas.
- Formulated with natural, refined oils.
- The coating is protected against infestation by blue stain fungi and mould.
- Good weather resistance on account of highly-effective UV absorbers.

AREAS OF APPLICATION

For all wooden structural elements in outdoor areas that are dimensionally stable or have limited or no dimensional stability, e.g. wooden houses, garden furniture, canopies, wooden cladding, balconies, etc. Colour: Colourless. Greying is delayed, but not completely prevented.

METHOD OF APPLICATION Paintbrush, do not spray on! CONSUMPTION $12 - 15 \text{ m}^2/1$ 750 ml, 2.5 l, 10 l **CONTAINER SIZES**

Color4You























Standard colours	
Java (mid-brown)	4402057056
Larch (light brown)	4402085967
Congo (dark brown)	4402057069
Colourless for	50546



Pullex Bodenöl

The oil of choice for terrace floors and other wooden floors in outdoor areas

- Highly penetrative wood oil for wooden terraces in outdoor areas.
- Optimal colour stabilisation for exotic woods and thermowood.
- Reduced cracking and greying of the wood.
- The coating is protected against infestation by blue stain fungi and mould.

AREAS OF APPLICATION

Horizontal wooden surfaces in outdoor areas that are not dimensionally stable, such as balcony floors, walkways, terraces, etc. Suitable for exotic woods, larch and modified woods.

METHOD OF APPLICATION Paintbrush $15 \, \text{m}^2/\text{l}$ CONSUMPTION **CONTAINER SIZES** 750 ml. 2.5 l

Color4You















Larch





Standard colours

Colourless

4419000200

4419050254





Pullex Teaköl

After-care oil for teak and other exotic woods

- Ready-to-use, biocide-free oil made from renewable raw materials for impregnation treatment and after-care of garden furniture made of teak and other hardwoods or exotic woods.
- · Very good penetrating capacity, excellent accentuation of the wood grain and a strong water repellent effect.
- Easy to apply using a cloth.

AREAS OF APPLICATION

For initial treatment and after-care of oiled garden furniture and for wood in interior finishing (e.g. bathrooms). For renovation projects, ideal in combination with Clean-Multi-Refresher.

METHOD OF APPLICATION

Apply by wiping on. Especially good results can be achieved by sanding with a sanding fleece. Apply once or twice, depending on the absorbency of the substrate.

CONSUMPTION

approx. 30 m²/l; wipe on thinly

CONTAINER SIZES 250 ml, 1 l























Base for tinting

Base W30

5347000030

Color4You





Pullex Aqua-Terra

Water-based, eco-friendly wood oil made from renewable raw materials

- Eco-friendly wood oil made from selected renewable raw materials, for interior and exterior use.
- Does not contain any of the active ingredients of chemical wood preservers or film protection products; no solvents or plasticisers.
- Natural, matt surfaces and pleasant feel.
- · Very good weather protection and highly durable.

AREAS OF APPLICATION

Wooden structural elements in outdoor areas that have no or only limited dimensional stability, e.g. wooden houses, wooden cladding, canopies, window shutters, balconies, gates, etc. Perfect for apiaries. Wall and ceiling elements made of wood in indoor areas.

METHOD OF APPLICATION Paintbrush $8 - 10 \text{ m}^2/\text{l}$ CONSUMPTION **CONTAINER SIZES** 750 ml, 2.5 l



















FOR INTERIOR USE



Standard colours

Colourless. tintable

30801

Color4You

Innenlasur

Water-based, silky gloss glaze for indoor use

- Water-thinnable glaze-finish coating made from an acrylate dispersion, for wood in indoor areas.
- Protection against dust and dirt.
- · Easy and quick to apply, pleasant smell, fast drying.
- Transparent, silky gloss wood shades and bright colours preserve the natural appearance of the wood.

AREAS OF APPLICATION

Wall and ceiling panelling, doors (use seals suitable for water-based paints!), furniture, wood panels, children's bedrooms, etc. Suitable for painting toys. For colourless or white transparent coatings on spruce (e.g. visible roof trusses, log cabin interiors ...), we recommend ADLER Innenlasur UV 100 (see below).

METHOD OF APPLICATION CONSUMPTION **CONTAINER SIZES**

Paintbrush, spray on. $10 - 12 \text{ m}^2/\text{l}$ 375 ml, 750 ml, 2.5l, 10l























Standard colours

UV 100 colourless tintable

5310000220

Color4You





Innenlasur UV 100

Water-based, dull matt natural effect with integrated UV filter

- Water-thinnable, breathable wood glaze offering outstanding protection against yellowing for visible roof trusses, panelling and the like.
- Contains effective light stabilisers to absorb UV radiation.
- Easy to apply.
- The transparent, dull matt finish ensures that the natural appearance of softwoods is retained.

AREAS OF APPLICATION

Visible roof trusses, wall and ceiling panelling. Not effective on hardwood species such as oak, meranti, mahogany, etc.


METHOD OF APPLICATION CONSUMPTION **CONTAINER SIZES**

Paintbrush approx. $10 - 12 \text{ m}^2/\text{l}$ 750 ml, 2.5l, 10 l





















STANDARD COLOURS INNENLASUR



Colourless, tintable

Color4You

STANDARD COLOURS INNENLASUR UV100



Innenlasur UV 100 Colourless



Innenlasur UV 100 Tanne



Innenlasur UV 100 Zugspitz



Innenlasur UV 100 Großglockner



Innenlasur UV 100 Mont Blanc

FOR INTERIOR USE



Standard colour

Colourless, tintable 7036000220

Color4You





Terra Wax-Oil

Eco-friendly, wax-based wood oil.

- Made from selected renewable raw materials, for interior use.
- Creates a refined, velvety, wax-like look.
- Guarantees a waterproof surface.
- Free from solvents, plasticisers and chemical ingredients.
- Cradle to Cradle Certified® silver certified and 100 % climate-neutral manufacturing process.
- Tested for use on toys (EN71-3) | Resistance to perspiration and saliva (DIN53160).

AREAS OF APPLICATION

Wall and ceiling panelling, wood panels, children's toys, log cabins, for interior use.

METHOD OF APPLICATION CONSUMPTION

350 ml, 750 ml, 2.5l, 10 l





















Paintbrush (acrylic brush), paint sprayer (compressed air)



Standard colours

7006000200 Colourless White 7006050000

Legno-Öl

Universal wood oil for interior use

- Easy to use
- Fast drying
- Durable, water and dirt-repellent
- Non-slip and anti-static
- Resistant to perspiration and saliva (ÖNORM S 1555)
- Suitable for children's toys (ÖNORM EN 71-3)
- For a pleasant feel
- Will not self-ignite

AREAS OF APPLICATION

Legno-Öl is a universal wood oil for furniture, wooden floors and interior finishing. Customers love its pleasant, natural feel. Also highly suitable for painting toys. This high-quality oil for use on wood is quick-drying and suitable for the treatment of both hardwoods and softwoods.

METHOD OF APPLICATION CONSUMPTION

Paintbrush, roller, wiping on, paint sprayer approx. $15 - 30 \text{ m}^2/\text{l}$

CONTAINER SIZES 750 ml, 2.5l, 5 l































Standard colour Colourless, tintable 7035000200

Legno Dura-Öl

Universal oil for the best possible protection and a natural look

- Natural surface and outstanding protection
- Very good chemical resistance
- Very little tendency to form shiny areas
- · Natural feel, flows beautifully
- Suitable for universal use
- No need to wipe off afterwards
- Freshen up if necessary with Legno Dura-Öl

AREAS OF APPLICATION:

For staircases and for building components that are fixed installations of a building, for kitchens, work surfaces, interior doors and furniture.

METHOD OF APPLICATION CONSUMPTION

Paintbrush, roller or paint sprayer approx. 20 m²/l 750 ml, 2.5 l





CONTAINER SIZES





















Standard colour

Colourless

7028000200

Legno-Zirbenöl

Oil with natural Swiss pine aroma, for interior use

- The natural characteristics of the Swiss pine are retained
- Will not self-ignite
- Perspiration and saliva resistance
- Suitable for children's toys (ÖNORM EN 71-3)
- Anti-static
- Rapid drying
- Easy to use
- Very good penetration capacity
- Very good water resistance
- Outstanding accentuation of the wood grain

AREAS OF APPLICATION

For furniture in living areas and interior finishing (wooden panelling, wooden ceilings, etc.). Legno-Zirbenöl is made predominantly from renewable raw materials and with pure, natural Swiss pine oil. The natural characteristics of the Swiss pine are retained.

METHOD OF APPLICATION CONSUMPTION

Paintbrush, roller, wiping on, paint sprayer approx. $15 - 30 \text{ m}^2/1$

CONTAINER SIZES 750 ml























FOR INTERIOR USE



Base for tinting

W30

50875

Color4You

Legno-Color

High-quality coloured wood oil for interior use

- Elegant, uniform colouration of the wood
- Pleasant feel
- Anti-static
- Exceptionally easy to use
- Very good penetration capacity
- Very good water resistance
- · Also very well suited to use on wood and parquet flooring

AREAS OF APPLICATION

For furniture in living areas, interior finishing (wooden panelling, wooden ceilings, etc.), wood and parquet flooring. Legno-Color is a coloured oil for treating both softwoods and hardwoods.

METHOD OF APPLICATION CONSUMPTION **CONTAINER SIZES**

Paintbrush, roller, wiping on, paint sprayer approx. $15 - 30 \text{ m}^2/\text{l}$ 750 ml, 2.51

























SELECTION OF POSSIBLE COLOURS LEGNO-COLOR



Ligurien



Navarra



Abruzzen



Toskana



Lombardei



Katalonien

Unlimited variety of colours thanks to the ADLER Color4You colour mixing system.





Standard colour

Colourless

7002000200



Legno-Hartwachsöl

Universal hard wax oil for interior use

- Pleasant feel
- Outstanding accentuation of the wood grain
- Perspiration and saliva-resistant
- Suitable for children's toys
- Anti-static
- Exceptionally easy to use
- Very good penetration capacity
- Very good water resistance
- Very good filling performance
- Solids content > 97%

AREAS OF APPLICATION

For furniture in living areas, interior finishing (wooden panelling, wooden ceilings, etc.), wood and parquet flooring. Legno-Hartwachsöl is a wood oil made from natural waxes and oils that ensures a healthy indoor atmosphere. The product is suitable for the treatment of both softwoods and hardwoods.

METHOD OF APPLICATION CONSUMPTION CONTAINER SIZES

Paintbrush, roller, wiping on, paint sprayer approx. 15 – 30 m²/l 750 ml, 2.5l



























Standard colour

Colourless

7008000210

Legno-Wachs

Universal wood wax for interior use

- Elegant, uniform colouration of the wood
- Velvety soft feel
- Pleasant to the touch
- Anti-static
- Will not self-ignite
- Exceptionally easy to use
- Very good penetration capacity
- Very good water resistance

AREAS OF APPLICATION

For furniture in living areas and interior finishing (wooden panelling, wood ceilings, etc.) which is not subject to much mechanical stress. Not suitable for use in splash water areas!

METHOD OF APPLICATION CONSUMPTION CONTAINER SIZES

Paintbrush, roller, wiping on, paint sprayer approx. $15 - 30 \text{ m}^2/\text{l}$ 750 ml, 2.5l























003

FOR INTERIOR USE



Standard colours

Legno-Reiniger Legno-Pflegeöl

7003000210 7009000210

Legno-Reiniger and -Pflegeöl

High-quality cleaner and universal after-care oil for furniture and interior fittings

- Easy to use
- Cleans and freshens up wood surfaces
- Mild odour
- Legno-Pflegeöl penetrates very well into the surface

AREAS OF APPLICATION

Legno-Pflegeöl is suitable for universal use and was developed to provide gentle after-care and freshening up of oiled furniture in living areas and in interior finishing (wooden panelling, wooden ceilings).

Legno-Reiniger is a colourless cleaner with only a mild odour, for use on all oiled wooden surfaces. This product has very good cleaning properties and is also suitable for use on greasy or oily marks.

METHOD OF APPLICATION Wipe on

CONSUMPTION Legno-Reiniger: approx. 50 m²/l

Legno-Pflegeöl: approx. 15 – 30 m²/l

CONTAINER SIZE Legno-Reiniger: 250 ml, 1l

Legno-Pflegeöl: 250 ml

















Set

Legno-Pflegeset 702900021001

Legno-Pflegeset

Practical set for cleaning and caring for oiled wood surfaces

AREAS OF APPLICATION

High-quality set for the regular cleaning and care of oiled wooden surfaces, e.g. furniture, wood and parquet floors and interior finishing.

CONTENTS

Legno-Reiniger 125 ml Legno-Pflegeöl 125 ml Sanding fleece Cleaning cloth Care instructions

METHOD OF APPLICATION CONTENTS ARE SUFFICIENT FOR Wipe on

approx. 6 m² per application (Legno-Reiniger) approx. 3.5 m² per application (Legno-Pflegeöl)





















Legno-Holzbodenseife

Cleans and cares for floors and gives them a great finish, with lasting results

- Concentrated care product for oiled, waxed and leached wood and parquet flooring, made from natural vegetable oils
- Removes dirt simply and powerfully in just one step
- Suitable for universal use also for other oiled surfaces, e.g. panelling
- Elegant matt effect, has an anti-static effect

AREAS OF APPLICATION

For the regular cleaning and care of oiled, waxed or leached wood and parquet flooring, as well as cork and laminate flooring in indoor areas.

METHOD OF APPLICATION Wipe on CONSUMPTION approx. 500 m² **CONTAINER SIZES** 11, 2.51 PRODUCT NUMBER 7031000210























Windoor-Care-Set

System for maintaining coated window frames and doors made of wood, aluminium or PVC

- All-in-one after-care set
- Can be used universally for windows, exterior doors and garden furniture
- For opaque and transparent surfaces
- Retains the degree of gloss, also for matt surfaces

AREAS OF APPLICATION

For the after-care of painted and varnished window frames, exterior door surfaces and garden furniture.

CONTENTS

ADLER Top-Cleaner 250 ml ADLER Top-Care 250 ml 2 spray heads 1 yellow cleaning cloth (Top-Cleaner) 1 blue maintenance cloth (Top-Care)

METHOD OF APPLICATION

CONTENTS IS SUFFICIENT FOR PRODUCT NUMBER

spray, wipe approx. 10 m² 7229000300





















PRODUCT OVERVIEW



Product Special properties Base **Special properties** Area of use Protective wood impregnation · | | | Pullex Imprägnier-Grund Solvent B, P, Iv treatment for raw wood **Pullex Renovier-Grund** Primer to brighten up weathered, greyed wood Solvent Protective wood impregnation Pullex Aqua-IG Water B, P, Iv treatment for raw wood Matt impregnation treatment and Pullex 2in1-Holzlasur Solvent FS weather protection all in one Pullex 3in1-Lasur Matt wood glaze Solvent Pullex Plus-Lasur FS Universal open-pore thin-film glaze finish Solvent Drip-inhibited thin-film glaze finish for **Pullex Top-Lasur** Solvent FS first-time coatings and renovation projects Drip-inhibited, matt wood glaze offering Pullex Top-Mattlasur Solvent FS excellent weather protection GLAZES Renovation glaze for windows and doors **Pullex Fenster-Lasur** Solvent **Protector Plus** Colourless glaze with strong water repellency Solvent FS 1111 **Pullex Silverwood** Metallic wood glaze Solvent FS **Pullex Platin** Special effect glaze with metallic effect Solvent FS Matt protective wood impregnation glaze, Pullex Aqua 3in1-Lasur Water FS water-based Pullex Aqua-DSL Thick-coat glaze finish for windows and doors Water **Pullex Color** Opaque, breathable wood paint Solvent FS Wood paint for efficient first-time coating and Pullex 2in1 Top-Color Solvent FS renovation projects **Pullex Aqua-Color** Opaque, water-based wood paint Water FS | | | | | | Pullex Holzöl UV protective oil for wooden facades Solvent Pullex Bodenöl Special oil for wooden floors in outdoor areas Solvent FS OILS Pullex Teaköl After-care oil for hardwoods and exotic woods Solvent Pullex Aqua-Terra Wood oil made from renewable raw materials Water Innenlasur Silky gloss wood glaze Water **FOR INTERIOR USE** Innenlasur UV 100 Dull matt wood glaze with UV filter Water Terra Wax-Oil Wood oil made from renewable raw materials Water Oils and Legno products Universal oils and waxes waxes

Only use Pullex Imprägnier-Grund and Pullex Aqua-IG if chemical wood protection is required. Offers protection against blue stain (EN 152-1) and wood-destroying fungi (EN 113) and prevents insect infestation (EN 46). Do not use wood preservers that contain biocides for large areas in indoor areas. For interior spaces, we recommend ADLER Innenlasur or ADLER VariColor.

FS The coating is protected against infestation by bluestain fungi and mould

B Protected against blue-stain fungi

P Protected against wood-destroying fungi

Iv Protected against insect infestation



Components that are not dimensionally stable (wooden houses, wooden cladding, canopies, balconies)



Limited dimensionally stable components (window shutters, balconies)



Dimensionally stable components (windows)



Exterior doors



Garden furniture



Wooden wall and ceiling elements in interior settings



Furniture



Floors (interior)

TOOLS & EQUIPMENT



SU 1 piece	
50 mm	952500030011
100 mm	952500030111

SOLVAMAXX PLUS

- Professional quality paintbrush for solvent-based paints, varnishes and glazes
- Has very fine polyester bristles and is solvent-resistant
- Available in 50 and 100 mm widths
- For solvent-based paints, varnishes and glazes
- Perfect coating results with no visible brush strokes
- Very hard-wearing and durable



SU 1 piece	
40 mm	950800030011
60 mm	950800030111
100 v 30 mm	050800030211

AQUAMAXX PLUS

- Professional quality paintbrush for water-based paints, varnishes and glazes
- For water-based paints and varnishes
- Highly elastic, keeps its shape, soft and supple
- Excellent paint uptake with even paint release
- Available in 40 mm and 60 mm widths and as a wallpaper smoothing brush 100 x 30 mm



SU 1 piece 50 mm 952300030011

BRUSH FOR APPLYING GLAZE HS 50

- High-quality paintbrush for applying transparent glazes
- This brush is made of Chinese bristle and is especially well suited to the renovation or first-time coating of windows with Pullex Fenster-Lasur
- The short bristles accentuate the grain of the wood particularly well



FLOOR BRUSH FOR OILS

- Suitable for the application of floor oils
- The high-quality natural bristles massage the oil into the wood to give perfect results





SU 1 piece 160 x 32 mm 952100030011

BRUSH FOR STAINING AND DUSTING OFF

- This fine brush is used for working in suitable water-based stains.
- It ensures that the stain penetrates into the pores of the wood and is evenly distributed.
- Can also be used for dusting off and cleaning any kind of surface.
- Bristle length: 60 mm



SU 1 piece

Article No. 959500030011

CRIMPED BRASS WIRE BRUSH WITH 4-ROWS

- For brushing down and cleaning old, weathered wooden surfaces.
- The gently curved wooden handle is very comfortable to hold and allows you to work with precision.
- The finely-crimped brass wire bristles remove residues of paint, getting deep into the pores of the wood.



SU 1 piece

Article No.

952200030011

BRASS WIRE BRUSH WITH STRAP

- This brush is for brushing down and cleaning old, weathered wooden surfaces and for brushing out debris from porous woods.
- The soft brass-wire bristles remove residues of paint and loose pieces of wood, getting deep into the pores of the wood.
- The large surface area of the brush enables even brushing of large areas.
- Size: approx. 215 x 100 mm.



SU 1 piece

Paint scraper 951000030011

SU 3 pieces

Replacement blades 951000030117

PAINT SCRAPER

- Paint scraper with interchangeable blade
- For removing old paint and varnish
- Perfect in combination with ADLER's paint stripping products



90 years ago, Johann Berghofer laid the foundation stone for ADLER and work was started to develop its own paints.

Much has changed since that time, but one thing has stayed the same: our passion for colour, which drives us day after day to work on the perfect surface coating.

Paint runs through our veins.







instagram.com/adlerlacke_official



youtube.com/@AdlerLacke

ADLER-COATINGS.COM

ADLER-Werk Lackfabrik · Johann Berghofer GmbH & Co KG
Bergwerkstraße 22 · A-6130 Schwaz/Tirol
T. +43 5242 6922-0 · info@adler-lacke.com

ADLER Deutschland GmbH · Kunstmühlstr. 14 · D-83026 Rosenheim · T. +49 8031 304 5174